

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF PORTIONS OF THE SOUTH AND EAST BOUNDARIES,
A PORTION OF THE SUBDIVISIONAL LINES,

A PORTION OF THE SUBDIVISION OF CERTAIN SECTIONS BY THE
THREE MILE METHOD,

THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS
AND

THE DEPENDENT RESURVEY OF MINERAL SURVEY No. 5519,

IN

TOWNSHIP 1 SOUTH, RANGE 1 EAST

OF THE UINTAH SPECIAL MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

M. Ross Workman
Supervisory Cadastral Surveyor

Under special instruction dated and approved **April 30, 2004**, which provided for the surveys included under Group Number **975**, and assignment instructions date **April 30, 2004**.

Survey commenced **May 25, 2004**
Survey completed **September 30, 2004**

INDEX DIAGRAM

Township 1 South, Range 1 East
 Uintah Special Meridian, Utah

6	5	4	3	2	1
7	62 8 61	47 9 46	35 10	11	12
18	59 17 58	44 16 43	34 15	14	13
19	55 20 54	41 21 40	32 22 30	23 25	19 24 19
30	52 29 50	39 28 37	29 27 27	23 26 22	17 25 12 16
31	48 32 9	36 33 6	25 34 5	20 35 4	14 36 11 3

The Subdivision of Section 16.....	Page 63
The Subdivision of Section 17.....	Page 65
The Subdivision of Section 20.....	Page 72
The Subdivision of Section 21.....	Page 77
The Subdivision of Section 25.....	Page 82
The Subdivision of Section 26.....	Page 87
The Subdivision of Section 27.....	Page 89
The Subdivision of Section 28.....	Page 95
The Subdivision of Section 29.....	Page 100
The Subdivision of Section 32.....	Page 104
The Subdivision of Section 33.....	Page 108
The Subdivision of Section 34.....	Page 114
The Subdivision of Section 35.....	Page 120
The Subdivision of Section 36.....	Page 124
Dependent Resurvey of Mineral Survey No. 5519.....	Page 127

T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of portions of the south and east boundaries, a portion of the subdivisional lines, a portion of the subdivision of certain sections by the three mile method, the survey of the subdivision of certain sections, and the dependent resurvey of Mineral Survey No. 5519, in T. 1 S., R. 1 E., Uintah Special Meridian, Utah.

History of Surveys

Surveyed by		Retr. or Resurveyed by	
SOUTH BOUNDARY			
All	C.L. DuBois	1875	
EAST BOUNDARY			
All	C.L. DuBois	1875	
Portion		A.D. Ferron	1890
WEST BOUNDARY (Uinta Special Meridian)			
All	C.L. DuBois	1875	
Portion		R.L. Houston	1998
NORTH BOUNDARY			
All	C.L. DuBois	1875	
Portion		R.L. Houston	1996
SUBDIVISION			
All	C.L. DuBois	1875	
Portion		R.L. Houston	1998

All of Mineral Survey Number 5519, surveyed by A.D. Ferron, under the Act of Congress, approved May 27, 1902.

NOTE: All of the subdivision of sections was surveyed by the three mile method.

NOTE: The Initial Point (NW Township Corner) was reestablished by A. Nelson in 1953.

NOTE: Several corners throughout this township were remonumented under a contract from the Bureau of Indian Affairs. They were remonumented, in 1958 and 1959, with a galvanized iron pipe, 2 1/2 inches diameter, with markings on a 3 inch diameter threaded galvanized cap attached.

The survey was executed in accordance with the specification set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions for Group No. 975, dated April 30, 2004.

This survey was executed with a Trimble 5800, Global Positioning System (GPS), using relative positioning techniques to establish a geographic position for each corner. The true geodetic mean bearings and the true horizontal ground distances were determined by inversing between the established positions.

T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

Preliminary to the resurvey, the lines of the prior surveys were retraced and a search was made for all corners and their calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

The geodetic control was derived from the U.S. Geological Survey Triangulation Station "SUNDANCE" as published by National Geodetic Surveys, is as follows:

Latitude: 40°22' 55.07875" N., Longitude: 109° 52' 59.91420" W.
N.A.D. 1983 (1994), N.A.V.D. 1988, Elevation: 5415 ft.

The geographic position of the 1/4 section corner of sections 1 and 36, on the south boundary of the township, as determined by G.P.S., using relative positioning techniques, from U.S. Geological Survey Triangulation Station "SUNDANCE" as published by National Geodetic Surveys, is as follows:

Latitude: 40°20' 44.768" N., Longitude: 109° 49' 52.226" W.
N.A.D. 1983 (1994), N.A.V.D. 1988, Elevation: 5150 ft.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Dependent Resurvey of a Portion of the South Boundary
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by C.L. DuBois in 1875

Beginning at the 1/4 section corner of sections 1 and 36, on the south boundary of the township, monumented with a sandstone, 16x8x6 inches, firmly set and dimly marked 1/4 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S36
1/4 ———
S1
T2S R1E
2004

Deposit the marked stone along side the aluminum post.

N. 89° 45.9' W., between sections 1 and 36.

19.939

The W 1/16 section corner of section 1 and 36, at the intersection of fences bearing north, south and west. This position is harmoniously related to other identified existing original corners in the area and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S36
W 1/16 ———
S1
T2S
2004

S. 89° 55.9' W., beginning new measurement.

19.985

Point for the corner of sections 1, 2, 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S	R1E
S35	S36
S2	S1
T2S	
2004	

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on the west shoulder of north and south paved road, 16 feet from its centerline.

S. 89° 55.9' W., between sections 2 and 35.

19.985 Point for the E 1/16 section corner of sections 2 and 35, at proportionate distance, falls in a hayfield, there is no remaining evidence of the original corner, not monumented.

39.970 The 1/4 section corner of sections 2 and 35, monumented with a 2 1/2 inches diameter, galvanized iron pipe, firmly set in the ground, projecting 13 inches above ground in an old torn down fence line with a 3 inch diameter threaded galvanized cap marked:

1959	
T1S	S35
R1E	
1/4	
T2S	S2
R1E	

This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

S. 89° 58.3' W., beginning new measurement.

19.968 Point for the W 1/16 section corner of sections 2 and 35, at proportionate distance, falls in a hayfield, there is no remaining evidence of the original corner, not monumented.

39.936 The corner of section 2, 3, 34, and 35, monumented with a 2 1/2 inches diameter, galvanized iron pipe, firmly set in the ground, projecting 14 inches above ground and leaning 6 inches to the east, with a 3 inch diameter, galvanized threaded cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

1959
T1S R1E
S34 | S35
S3 | S2
T2S R1E

This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

This corner falls in a fence that bears north and south, and at the base of a 16 inches diameter cottonwood tree.

N. 89° 58.7' W., between sections 3 and 34.

19.988

Point for the E 1/16 section corner of sections 3 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S34
E 1/16 ———
S3
T2S R1E
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Corner is located about 50 links distance north of a canal that drains east.

39.976

The 1/4 section corner of sections 3 and 34, monumented with a sandstone 15x12x8 inches, firmly set and plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
S34
1/4 ———
S3
T2S R1E
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit the marked stone alongside the aluminum post.

Corner is located 3 ft. west of a north and south fence and 30 ft. south of a fence that bears west. Also, 50 links north of a canal that drains east.

N. 89° 46.1' W., beginning new measurement.

20.040

The W 1/16 section corner of sections 3 and 34, monumented with a sandstone 18x12x8 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
S34
W 1/16 ———
S3
T2S R1E
2004

Deposit the marked stone alongside the aluminum post.

Corner is located 40 links south of an east and west fence, and about 50 links north of a canal draining east.

S. 89° 54.4' W., beginning new measurement.

19.938

Point for the corner of sections 3, 4, 33 and 34, at proportionate distance, falls on the west edge of a gravel road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap flush with the road, with a magnet at base, with aluminum cap marked:

T1S R1E
S33 | S34
S4 | S3
T2S
2004

Corner is located 25 links north of an east and west fence, with a cattle guard across road.

S. 89° 54.4' W., between sections 4 and 33.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 19.938** Point for the E 1/16 section corner of sections 4 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap flush with the road, with a magnet at base, with aluminum cap marked:

T1S R1E
S33
E 1/16 ———
S4
T2S
2004

Corner is located on the south edge of an east and west gravel road, 33 links north of an east and west fence, and in line with a fence to the north.

- 39.876** Point for the 1/4 section corner of sections 4 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap flush with the road, with a magnet at base, with aluminum cap marked:

T1S R1E
S33
1/4 ———
S4
T2S
2004

Corner is located on the south edge of an east and west gravel road.

- 52.252** Intersect line 1-4, Duchesne No. 7 Lode, Mineral Survey No. 5519.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap flush with the road, with a magnet at base, with aluminum cap marked:

CCC
T1S R1E
S33
MS 5519 S4
D7 T2S R1E
2004

Corner is located on the south edge of an east and west gravel road, 32.3 links north of an east and west fence line.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS**59.814**

Point for the W 1/16 section corner of sections 4 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with aluminum cap flush with the road, with a magnet at base, with aluminum cap marked:

T1S R1E
S33
W 1/16 ———
S4
T2S
2004

Corner is located on south edge of an east and west gravel road, and in alignment with fence to the south.

63.666

Intersect line 2-3, Duchesne No. 7 Lode, Mineral Survey No. 5519.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 32 inches in the ground, with aluminum cap 2 inches below the road surface, with a magnet at base, with aluminum cap marked:

CCC
T1S R1E
MS 5519
S33 — D7
S4 T2S
2004

Corner is located 4.5 ft. south of centerline of an east and west gravel road, 48 links south of an east and west fence line.

79.752

Point for the corner of sections 4, 5, 32 and 33, at distance - distance intersect from the section corner of sections 5, 6, 31 and 32 and the 1/4 section corner of sections 32 and 33, utilizing the Uintah Engineering & Land Surveying Plat dated 12-28-89. This point falls on the north shoulder of a paved highway, is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Set a railroad spike flush with the pavement.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 60° 16.2' W., 149.6 links distance, with aluminum cap marked: RM T2S R1E S5 98.7 FT 2004, with arrow pointing to the corner.

Raise a small mound of stone to the west of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, 1 ft. south of an east and west R/W fence on north side of road; for a reference monument, bears N. 42° 11.6' W., 86.1 links distance, with aluminum cap marked: RM T1S R1E S32 56.8 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

N. 89° 53.4' W., between sections 5 and 32.

20.035

Point for the E 1/16 section corner of sections 5 and 32 at proportionate distance, falls on the north edge of a paved highway, there is no remaining evidence of the original corner.

Set a PK nail flush with the pavement.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base on south side of road, for a reference monument, bears S. 54° 44.4' W., 96.7 links distance, with aluminum cap marked: RM T2S R1E E 1/16 S5 63.8 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base 1 ft. south of an east and west right-of-way fence on north side of road, for a reference monument, bears N. 59° 46.2' W., 80.8 links distance, with aluminum cap marked: RM T1S R1E E 1/16 S32 53.3 FT 2004, with arrow pointing to the corner.

40.070

Point for the 1/4 section corner of sections 5 and 32, at proportionate distance, utilizing the Uintah Engineering & Land Surveying Plat dated 12-28-89. This point falls in the west bound lane of the paved highway.

Set a railroad spike flush with the pavement.

From which

A cross "X", on the east end of the headwall of a culvert, bears S. 42° 36.6' W., 65.8 links distance.

A U.S.G.S. B.M. marked: U.S. GEOLOGICAL SURVEY BENCH MARK 40 EAM 1964 ELEVATION ABOVE SEA 5360 FEET, is located on east end of a headwall with additional scribing " EIE EG95A", bears N. 49° 14.2' W., 56.8 links distance.

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. 89° 50.5' W., beginning new measurement.

20.036

Point for the W 1/16 section corner of sections 5 and 32, at proportionate distance, falls on the north side of the west bound lane, there is no remaining evidence of the original corner.

Set a railroad spike flush with the pavement.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, 1 ft. north of an east and west R/W fence, bears S. 41° 53.5' W., 73.3 links distance, with aluminum cap marked: RM T2S R1E W 1/16 S5 48.4 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, 1 ft. south of an east and west R/W fence, bears N. 38° 25.6' W., 76.5 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S32 50.5 FT 2004, with arrow pointing to the corner.

40.072

The corner of section 5, 6, 31 and 32, monumented with a RLS UINTAH COUNTY SUR, 1/2 inch rebar protruding 5 inches above ground in a small mound of stone, with a 1 1/4 inch cap marked:

RLS UINTAH COUNTY

31 | 32
6 | 5

SURVEY

This position is harmoniously related to other identified original corners in the area, this corner is accepted as the best available evidence of the original corner position.

Corner is located in a tree line on the south side of an east and west dirt road.

From this corner, the corner of section 1, 6, 31 and 36, the southwest corner of the township, on the Uintah Special Meridian, bears S. 89° 54.1' W., 79.908 chains distance, monumented with a rod, 5 inches under the surface of the road. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

A reference monument, monumented with a 1 inch aluminum rod with a 2 inch cap, marked: RM UINTAH

**DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

COUNTY SURVEY, with arrow pointing to the corner, bears S. 57° 56.5' W., 86.8 links distance. (57.3 ft.)

A reference monument, monumented with a 1 inch aluminum rod with a 2 inch cap, marked: RM UINTAH COUNTY SURVEY, with arrow pointing to the corner, bears N. 59° 31.3' W., 94.1 links distance. (62.1 ft.)

Dependent Resurvey of a Portion of the East Boundary
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by C.L. DuBois in 1875
and the Dependent Resurvey by A.D. Ferron in 1890

From the 1/4 section corner, of sections 31, and 36, on the the east boundary of the township, monumented with a 5/8 inch rebar, with a 1 1/2 inch aluminum cap marked: UELS 1/4 S36 S31 143961 LCK. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S
R1E R2E
1/4
S36 | S31
2004

Deposit rebar and cap inside the aluminum post.

Corner is located on the north side of a fence post, at the beginning of a fence projecting to the south.

N. 0° 06.8' E., between sections 31 and 36, on the east boundary of the township.

19.970

Point for the N 1/16 section corner of sections 31 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S
R1E R2E
N 1/16
S36 | S31
2004

Raise a mound of stone to the west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on a south slope.

39.940

Point for the corner of sections 25, 30, 31 and 36, at proportionate distance, falls on the center line of a paved road, bears east and west, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 36° 58.8' E., 78.0 links distance, with aluminum cap marked: RM T1S R1E R2E 51.5 FT S30 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 53° 51.8' W., 56.1 links distance, with aluminum cap marked: RM T1S R1E R2E S25 37.0 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Reestablishment of the Survey Executed by C. L. DuBois in 1875

N. 0° 06.8' E., between sections 25 and 30.

19.970

The S 1/16 section corner of sections 25 and 30, monumented with a 1/2 inch rebar flush with the center line of a paved road, bearing north and curving to the southwest and in line with fences to the east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

A right-of-way marker on east side of road, bears N. 15° 17.3' E., 2.390 chains distance.

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 75° 39.6' W., 59.6 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S25 39.3 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 37° 24.9' W., 76.4 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S25 50.4 FT 2004, with arrow pointing to the corner.

N. 0° 07.6' E., beginning new measurement.

20.266

The 1/4 section corner of sections 25 and 30, monumented with a drive gear rod, flush with the surface on the west edge of the south bound lane of paved road, in line with fences to the east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position

From which

A right-of-way marker on east side of paved road, bears N. 58° 36.2' E., 55.8 links distance.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 52° 38.0' W., 56.8 links distance, with aluminum cap marked: RM T1S R1E E 1/4 S25 37.5 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 65° 28.2' W., 51.1 links distance, with aluminum cap marked: RM T1S R1E 33.7 FT E 1/4 S25 2004, with arrow pointing to the corner.

N. 0° 16.6' E., beginning new measurement.

19.676

Point for the N 1/16 section corner of sections 25 and 30, at proportionate distance, falls 5.2 ft. west of center line of north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

**DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 49° 46.0' W., 71.5 links distance, with aluminum cap marked: RM T1S R1E N 1/16 S25 47.2 ft. S30 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, with a magnet at base, for a reference monument, bears N. 89° 09.0' W., 54.4 links distance, with aluminum cap marked: RM T1S R1E N 1/16 S25 35.9 FT 2004, with arrow pointing to the corner.

39.352

The corner of sections 19, 24, 25 and 30, monumented with a 3/4 inch rebar and a destroyed plastic cap, located in the north and south paved road and in line with a fence to the west and a fence to the east on the south side of a gravel road. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 26 inches in the ground, with a magnet at base, for a reference monument, bears S. 69° 34.3' E., 50.9 links distance, with aluminum cap marked: RM T1S R2E S30 33.6 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 28 inches in the ground, with a magnet at base, for a reference monument, bears S. 68° 29.1' W., 51.7 links distance, with aluminum cap marked: RM T1S R1E S25 34.1 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by C.L. DuBois in
1875

From the corner of sections 1, 2, 35 and 36, on the south boundary of the township, hereinbefore described.

N. 0° 15.2' E., between sections 35 and 36.

19.959

Point for the S 1/16 section corner of sections 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S 1/16
S35 | S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on a south edge of a hay field.

39.918

Point for the 1/4 section corner of sections 35 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S35 | S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in thick brush in the bottom of a draw, drains west.

59.877

True point for the N 1/16 section corner of sections 35 and 36, at proportionate distance, falls in an irrigation ditch, there is no remaining evidence of the original corner.

True point is located 27.3 links north of an east and west fence line and 15.2 links west of a north and south fence line.

79.836

Point for the corner of sections 25, 26, 35 and 36, at proportionate distance, falls in an east and west gravel road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the gravel road. This corner spike is located 24.2 links east of a fence that projects south on the south side of road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 37° 56.9' E., 52.7 links distance, with aluminum cap marked: RM T1S R1E S25 34.8 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

This RM is located in an east and west fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 48° 54.1' E., 88.0 links distance, with aluminum cap marked: RM T1S R1E S36 58.1 FT 2004, with arrow pointing to the corner.

This RM is located in an east and west fence line.

From the corner of section 25, 30, 31 and 36, on the east boundary of the township, hereinbefore described.

N. 89° 59.6' W., between sections 25 and 36.

19.844

Point for the E 1/16 section corner of sections 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S25
E 1/16 ———
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 22.7 links north of the centerline of an east and west gravel road.

29.766

Point for the W-E 1/64 section corner of sections 25 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S25
W-E 1/64 ———
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 33 links north of an east and west gravel road on top of a ditch bank.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS**39.688**

Point for the 1/4 section corner of sections 25 and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S25
1/4 —————
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 25 links north of the centerline of a gravel road, 9 links west of a canal that flows south, and 20 links west of a fence on the south side of road that projects south.

59.532

Point for the W 1/16 section corner of sections 25 and 36, at proportionate distance, falls on the north edge of a gravel road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the gravel road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 11° 04.8' E., 68.5 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S36 45.2 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 71° 51.7' W., 119.7 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S25 79.0 FT 2004, with arrow pointing to the corner.

This RM is located at the corner of a steel fence line projecting northeast and west.

79.376

The corner of sections 25, 26, 35 and 36.

N. 0° 43.1' W., between sections 25 and 26.

19.961

Point for the S 1/16 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
S 1/16
S26 | S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 15 links east of a wash, drains south.

39.922

The 1/4 section corner of sections 25 and 26, determined at the corner of fences that project north and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S26 | S25
2004

N. 0° 30.5' W., beginning new measurement.

20.063

The N 1/16 section corner of sections 25 and 26, determined at the corner of fences that projects north, south and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S26 | S25
2004

N. 0° 08.9' W., beginning new measurement.

20.068

Point for the corner of sections 23, 24, 25 and 26, determined latitudinally by proportionate measurement and longitudinally by a fence line, extending north and south.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S23 S24
S26 S25
2004

Corner is located 15 links west of a north and south pipeline.

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

N. 89° 39.8' W., between sections 24 and 25.

- 20.091** Point for the E 1/16 section corner of sections 24 and 25, at proportionate distance, falls in a corral, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S24
E 1/16 ———
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 75 links east of a hay stack, 3.00 chains long, bears north and south.

- 40.182** Point for the 1/4 section corner of sections 24 and 25, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

- 60.273** Point for the W 1/16 section corner of sections 24 and 25, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

- 80.364** The corner of sections 23, 24, 25 and 26.
-

N. 0° 18.0' E., between sections 23 and 24.

- 20.068** The S 1/16 section corner of sections 23 and 24, at the corner of fences that project north, south and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S 1/16
S23 | S24
2004

From the corner of sections 2, 3, 34 and 35, on the south boundary of the township, hereinbefore described.

N. 0° 03.3' W., between sections 34 and 35.

19.880

Point for the S 1/16 section corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S 1/16
S34 | S35
2004

Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 4 links east of a north and south fence line.

39.760

Point for the 1/4 section corner of sections 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S34 | S35
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 13.1 links north of an east and west fence line and 25 links east of a north and south fence line.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

49.700 Point for the S-N 1/64 section corner of sections 34 and 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S-N 1/64
S34 | S35
2004

Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in the bottom of a draw, drains northwest.

59.640 Point for the N 1/16 section corner of sections 34 and 35, at proportionate distance, the original sandstone 18x9x3 inches, plainly marked 1/16, was found lying loose next to a power pole.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S34 | S35
2004

Deposit the sandstone alongside the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 30.3 links south of a power pole.

79.520 Point for the corner of sections 26, 27, 34 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S27 | S26
S34 | S35
2004

Raise a mound of stone 4 ft. base, 2 ft. high, west of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a 5 ft. steel fence post alongside the aluminum post.

From the corner of sections 25, 26, 35 and 36.

S. 89° 43.4' W., between sections 26 and 35.

20.080

Point for the E 1/16 section corner of sections 26 and 35, at proportionate distance, falls on the centerline of a gravel road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road. This spike is 9 links west of a fence projecting to the south, and 15 links east of a fence projecting to the north.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 51° 10.0' W., 83.0 links distance, with aluminum cap marked: RM T1S R1E E 1/16 S35 54.8 FT 2004, with arrow pointing to the corner.

Reference monument is located on south side of gravel road in east and west fence line at east end of a gate.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 73° 58.1' W., 63.5 links distance, with aluminum cap marked: RM T1S R1E E 1/16 S26 41.9 FT 2004, with arrow pointing to the corner.

Reference monument is located in an east and west fence line north of road.

40.160

Point for the 1/4 section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S26
1/4 ———
S35
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 30.3 links south of the centerline of a dirt road, bears east and west, and 53.0 links south of an east and west fence line.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 60.240** Point for the W 1/16 section corner of sections 26 and 35, at proportionate distance, falls in a north and south fence line, there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:
- T1S R1E
S26
W 1/16 —————
S35
2004
- Set a 5 ft. steel fence post alongside the aluminum post.
- 80.320** The corner of sections 26, 27, 34 and 35.
-
- N. 0° 09.0' E., between sections 26 and 27.
- 4.970** Point for the S-S-S 1/256 section corner of sections 26 and 27.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:
- T1S R1E
S-S-S 1/256
S27 | S26
2004
- Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.
- Set a 5 ft. steel fence post alongside the aluminum post.
- 19.880** Point for the S 1/16 section corner of sections 26 and 27, at proportionate distance, there is no remaining evidence of the original corner.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:
- T1S R1E
S 1/16
S27 | S26
2004
- Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 31.1 links south of an east and west fence line and 50.0 links east of drainage, drains southeast.

39.760

Point for the 1/4 section corner of sections 26 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S27 | S26
2004

Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

59.640

The N 1/16 section corner of sections 26 and 27, monumented with a sandstone, 10x10x7 inches, firmly set, dimly marked 1/16 on west face, and old wood post alongside.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
N 1/16
S27 | S26
2004

Deposit the marked stone alongside the aluminum post.

N. 1° 07.2' W., beginning new measurement.

20.028

Point for the corner of sections 22, 23, 26 and 27, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

From this point, the 1/4 section corner of sections 22 and 23, bears N. 1° 24.7' E., 40.061 chains distance, monumented with a 5/8 inch rebar, with an orange cap marked: RLS UT PLS 161259. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position, not remonumented.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

A careful search was made for the S 1/16 section corner, which was not recovered.

The rebar is located at the corner of fences, projecting east, west and south.

From the corner of sections 23, 24, 25 and 26.

S. 89° 26.6' W., between sections 23 and 26.

- 19.952 Point for the E 1/16 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner, not monumented.
- 39.904 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner, not monumented.
- 59.856 Point for the W 1/16 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner, not monumented.
- 79.808 The point for the corner of sections 22, 23, 26 and 27.

From the corner of sections 3, 4, 33 and 34, on the south boundary of the township, hereinbefore described.

N. 0° 06.8' W., between sections 33 and 34.

- 19.995 Point for the S 1/16 section corner of sections 33 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
S 1/16
S33 | S34
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located, 6.8 links north and 19.7 links east from a fence corner with fences projecting north, south and west. Also 23.5 links west of the centerline of a north and south gravel road with a cattle guard, and 47.0 links west of the right-of-way fence.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

39.990 True point for the 1/4 section corner of sections 33 and 34, at proportionate distance, falls on an oil pipe line, there is no remaining evidence of the original corner.

40.075 Point selected for the witness corner to the 1/4 section corner of sections 33 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

WC
T1S R1E
1/4
S33 ↓ S34
2004

Witness corner is located 1.5 links east of a north and south fence line.

59.985 The N 1/16 section corner of sections 33 and 34, determined at the corner of fences that project south and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R1E
N 1/16
S33 | S34
2004

N. 0° 00.6' W., beginning new measurement.

19.997 The corner of sections 27, 28, 33 and 34, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, and in a collar of stone, projecting 10 inches above ground, with a 3 inch threaded galvanized cap unmarked. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Rebuild collar of stone around iron pipe and marked the cap to read:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
S28 | S27
S33 | S34
 BLM
 2004

From the corner of sections 26, 27, 34 and 35.

N. 89° 37.1' W., between sections 27 and 34.

9.998 Point for the E-E 1/64 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
 S27
 E-E 1/64 ———
 S34
 2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 10 links west of a small drainage and 53 links west of centerline of large drainage, both draining southerly.

19.996 Point for the E 1/16 section corner of sections 27 and 34, at proportionate distance, there is no remaining evidence of the original witness corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
 S27
 E 1/16 ———
 S34
 2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in a swampy meadow.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 39.677** Point selected for the witness corner to the 1/4 section corner of sections 27 and 34, there is no remaining evidence of the original witness corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

WC
T1S R1E
S27
1/4 ←
S34
2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

- 39.992** True point for the 1/4 section corner of sections 27 and 34, falls in creek, 15 ft. wide and 3 ft. deep, drains southeast.

- 49.990** Point for the E-W 1/64 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S27
E-W 1/64 —
S34
2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 27.3 links east of a north and south fence line.

- 54.989** Point for the W-E-W 1/256 section corner of sections 27 and 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S27
W-E-W 1/256 —
S34
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Raise a mound of stone 2 ft. base, 1 1/2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

59.988

Point for the W 1/16 section corner of sections 27 and 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S27
W 1/16 ———
S34
2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

79.984

The corner of sections 27, 28, 33 and 34.

N. 0° 07.7' W., between sections 27 and 28.

19.942

The S 1/16 section corner of sections 27 and 28, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 10 inches above ground, with a 3 inch threaded galvanized cap unmarked. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Marked the cap to read:

S 1/16
S28 | S27
BLM
2004

Corner is located at the corner of fences which project north and east.

N. 0° 18.5' W., beginning new measurement.

20.442

The 1/4 section corner of sections 27 and 28, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground, with a 3 inch threaded galvanized cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

1959
S28 1/4 S27

This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Added the marks, BLM 2004, to the cap.

N. 0° 12.4' E., beginning new measurement.

- 19.932** The N 1/16 section corner of sections 27 and 28, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 10 inches above ground, with a 3 inch threaded galvanized cap marked:

1959
S28 1/16 S27

This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Added the marks, BLM 2004, to the cap.

N. 0° 11.0' E., beginning new measurement.

- 19.869** The corner of sections 21, 22, 27 and 28, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, projecting 14 inches above ground, with a 3 inch threaded galvanized cap marked:

1959

S21	S22
S28	S27

Added the marks, BLM 2004, to the cap.

Corner is located 1.5 links east of a fence corner with fences projecting west and south, and 18 links south of an east and west dirt road.

This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From the point for the corner of section 22, 23, 26 and 27.

N. 89° 14.5' W., between sections 22 and 27.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS**19.938**

Point for the E 1/16 section corner of sections 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S22
E 1/16 ———
S27
2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

39.876

Point for the 1/4 section corner of sections 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S22
1/4 ———
S27
2004

Raise a mound of stone 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

59.814

Point for the W 1/16 section corner of section 22 and 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to rock, with a magnet at base, in a mound of stone, 6 ft. base to top of aluminum cap marked:

T1S R1E
S22
W 1/16 ———
S27
2004

Set a 5 ft. steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 60.6 links west of a north and south fence line and 18.2 links south of a gravel road, bears east and west.

79.752 The corner of sections 21, 22, 27 and 28.

N. 0° 19.9' E., between sections 21 and 22.

19.945 The S 1/16 section corner of sections 21 and 22, monumented with a sandstone, 14x9x7 inches, firmly set and plainly marked 1/16 on west face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S 1/16
S21 | S22
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

Corner is located in sagebrush, 30 links west of a wash, drains south.

N. 0° 00.6' E., beginning new measurement.

20.053 Point for the 1/4 section corner of sections 21 and 22, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with a magnet at base, with aluminum cap flush with the ground and marked:

T1S R1E
1/4
S21 | S22
2004

Raise a mound of stone 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 15 links north of an east and west fence line.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS**40.106**

The N 1/16 section corner of sections 21 and 22, monumented with a rebar at a fence corner, with fences projecting north, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S21 | S22
2004

Deposit rebar inside of the aluminum post.

Raise a mound of stone 3 ft. base, 2 ft. high, northwest of the aluminum post.

N. 0° 00.3' E., beginning new measurement.

20.026

The corner of sections 15, 16, 21 and 22, monumented with a sandstone, 15x12x7 inches, firmly set and plainly marked with 3 notches on the south and 3 notches on the east edges.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S16 | S15
S21 | S22
2004

Deposit the marked stone alongside the aluminum post.

Corner is located 1.3 links west and 1.5 links south of a fence corner, with fences projecting east, west and south.

From the N 1/16 section corner of sections 15 and 16, monumented with a sandstone, 15x8x8 inches, firmly set and plainly marked 1/16 on west face.

At the corner point.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S16 | S15
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone 4 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on a sagebrush flat about 1.00 chain north of an east and west fence line, and about 1.5 chains west of a north and south fence line.

N. 0° 04.9' E., between sections 15 and 16.

19.985

Point for the corner of sections 9, 10, 15 and 16, at proportionate distance, falls 26.4 link north of the centerline of Utah State Highway No. 121, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 47° 16.7' E., 66.8 links distance, with aluminum cap marked: RM T1S R1E S10 44.1 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 36° 40.4' W., 56.7 links distance, with aluminum cap marked: RM T1S R1E S9 37.4 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

A 5/8 inch rebar with an orange cap marked: RMS UT PLS 161259, bears N. 54° 23.7' W., 81.1 links distance, this rebar was not used in the course of this survey.

From this corner, the corner of section 7, 12, 13 and 18, on the east boundary of the Township, bears S. 89° 51.3' E., forward bearing, N. 89° 49.1' W., back bearing 239.872 chains distance,

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

monumented with a 1 1/2 inch diameter Uintah County Survey cap flush with the pavement marked UINTAH COUNTY SURVEY, located at the intersection of Utah State Highway No. 121, which bears east and west, and a paved county road that bears south, also in line with a fence to the north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

The control line was fully retraced and no evidence of the intervening corners was found.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 61° 02.9' W., 76.5 links distance, with aluminum cap marked: RM T1S R1E S13 50.5 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 52° 23.8' W., 77.4 links distance, with aluminum cap marked: RM T1S R1E S12 51.1 FT 2004, with arrow pointing to the corner.

N. 0° 12.5' W., between sections 9 and 10.

19.985 Point for the S 1/16 section corner of sections 9 and 10, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

39.970 Point for the 1/4 section corner of sections 9 and 10, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

From this point, a fence corner with fences projecting east, west and south, bears S. 62° 22.9' W., 0.202 chains distance.

59.955 The N 1/16 section corner of sections 9 and 10, monumented with a sandstone 20x10x9 inches, firmly set and plainly marked 1/16 on the west face.

At the corner point.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S9 | S10
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone 4 ft. base, 2 ft. high, west of the aluminum post.

From the corner of sections 4, 5, 32 and 33, on the south boundary of the township, hereinbefore described.

N. 0° 50.9' W., between sections 32 and 33.

20.068

Point for the S 1/16 section corner of sections 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R1E
S 1/16
S32 | S33
2004

Corner is located in an east and west fence and 19 links east of a north and south fence line.

40.136

The 1/4 section corner of section 32 and 33 monumented with a 5/8 inch rebar, projecting 3 inches above ground, alongside a wood post, 3 inches square, 36 inches long, dimly scribed with markings visible. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S32 | S33
2004

Rebar was set inside the aluminum post.

Deposit wood post alongside the aluminum post.

N. 0° 29.4' E., beginning new measurement.

20.001

Point for the N 1/16 section corner of section 32 and 33, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S32 | S33
2004

Corner is located 4.5 links south of an east and west fence, 12 links east of a fence that projects north and 18 links east of a fence that projects south.

40.002

The corner of sections 28, 29, 32 and 33, monumented with a 5/8 inch rebar, 6 inches below the surface of the road. This position is harmoniously related with identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $41^{\circ} 56.6'$ E., 70.5 links distance, with aluminum cap marked: RM T1S R1E S28 46.5 FT 2004, with arrow pointing to the corner.

Reference monument is located on north side of road, 1.5 links south of an east and west fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears S. $65^{\circ} 48.6'$ E., 69.7 links distance, with aluminum cap marked: RM T1S R1E S33 46.0 FT 2004, with arrow pointing to the corner.

Reference monument is located on south side of road, 2 links north of an east and west fence line.

From the corner of sections 27, 28, 33 and 34.

S. $89^{\circ} 55.5'$ W., between sections 28 and 33.

19.984

The E 1/16 section corner of sections 28 and 33, monumented with a sandstone 13x8x8 inches, with marks obliterated.

At the corner point

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S28
E 1/16 ———
S33
2004

Deposit the stone alongside the aluminum post.

N. 89° 51.5' W., beginning new measurement.

19.900

Point for the 1/4 section corner of section 28 and 33, determined latitudinally on the north side of a road in an east and west fence line, and longitudinally aligned with a fence on south side of road, projecting south. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
S28
1/4 ———
S33
2004

Corner is located 50 links west of a fence corner, with fences projecting north and west, and 36.4 links north of a fence corner, with fences projecting west and south.

S. 89° 59.6' W., beginning new measurement.

19.993

Point for the W 1/16 section corner of sections 28 and 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches to surface of ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S28
W 1/16 ———
S33
2004

Corner is located on north edge of gravel road.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

39.986 The corner of sections 28, 29, 32 and 33.

N. 0° 13.0' W., between sections 28 and 29.

20.058 Point for the S 1/16 section corner of sections 28 and 29, at proportionate distance, falls on the west edge of a gravel road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 42° 05.3' E., 79.9 links distance, with aluminum cap marked: RM T1S R1E S28 52.7 FT S 1/16 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 38° 58.9' E., 90.0 links distance, with aluminum cap marked: RM T1S R1E S28 59.3 FT S1/16 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

40.116 Point for the 1/4 section corner of sections 28 and 29, at proportionate distance, falls on the west edge of a gravel road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, and flush with the west shoulder, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S29 | S28
2004

A light pole base bears S. 65° W., 33.3 links distance.

60.174 Point for the N 1/16 section corner of sections 28 and 29, at proportionate distance, falls in an east and west fence line west of a gate, there is no remaining evidence of the original corner, not monumented.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
N 1/16
S29 | S28
2004

Set a 5 ft. steel fence post alongside the aluminum post.

80.232

Point for the corner of sections 20, 21, 28 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S20 | S21
S29 | S28
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in thick brush. A fence corner, bears N. 86° 31.4' W., 54.6 links distance, fences project south and west.

From the corner of sections 21, 22, 27 and 28.

N. 89° 40.9' W., between sections 21 and 28.

19.862

The E 1/16 section corner of sections 21 and 28, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, projecting 14 inches above ground, with the original sandstone, 22x12x12 inches deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S21
1/16
S28

Added the marks, BLM 2004, to the cap.

Corner is located 3 links east and 1.5 links north of a fence corner, with fences projecting north and east.

S. 89° 52.8' W., beginning new measurement.

20.097

Point for the 1/4 section corner of sections 21 and 28, at proportionate distance, falls on the west side of a drainage, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S21
1/4 ———
S28
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

40.194

The W 1/16 section corner of sections 21 and 28, monumented with a sandstone 11x11x6 inches, firmly set and dimly marked 1/16 on the north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S21
W 1/16 ———
S28
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

N. 89° 52.9' W., beginning new measurement.

20.081

The corner of sections 20, 21, 28 and 29.

N. 0° 09.5' E., between sections 20 and 21.

20.058

The S 1/16 section corner of sections 20 and 21, monumented with a sandstone 14x9x8 inches, firmly set and plainly marked 1/16 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
S 1/16
S20 | S21
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Corner is located 23 links west of a north and south trail road.

N. 0° 02.4' E., beginning new measurement.

20.028

The 1/4 section corner of sections 20 and 21, monumented with a sandstone 14x11x10 inches, firmly set and plainly marked 1/4 on the west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S20 | S21
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

N. 0° 28.5' E., beginning new measurement.

20.039

Point for the N 1/16 section corner of sections 20 and 21, determined by the corner of fences that project north, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point on south side of fence post.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S20 | S21
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

N. 0° 17.6' E., beginning new measurement.

20.028

The corner of sections 16, 17, 20 and 21, monumented with a sandstone 15x11x6 inches, dimly marked, with a 1/2 inch rebar alongside.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E	
S17	S16
S20	S21
2004	

Deposit the marked stone and rebar alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Corner is located in thick Russian olive trees, in a north and south fence line, 53 links north of an east and west fence line.

From the corner of sections 15, 16, 21 and 22.

N. 89° 36.3' W., between sections 16 and 21.

19.917

Point for the E 1/16 section corner of sections 16 and 21, determined latitudinally on line and longitudinally at record distance, 32 links west of the small dry creek, 3 links wide and drains south.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E	
S16	
E 1/16	_____
S21	
2004	

Raise a mound of stone, 4 ft. base, 3 ft. high, north of the aluminum post.

Corner is located in an east and west fence line, 30 links south of the centerline of an east and west gravel road.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 41.080** The 1/4 section corner of sections 16 and 21, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, projecting 8 inches above ground, with the original sandstone, 16x12x8 inches deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S16
——— 1/4
S21

Added the marks, BLM 2004, to the cap.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the galvanized pipe.

S. 89° 47.9' W., beginning new measurement.

- 19.415** Point for the W 1/16 section corner of sections 16 and 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S16
W 1/16 ———
S21
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

- 38.830** The corner of sections 16, 17, 20 and 21.

N. 0° 04.6' W., between sections 16 and 17.

- 20.024** Point for the S 1/16 section corner of sections 16 and 17, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
S 1/16
S17 | S16
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 47.0 links east of the corner of a fence, with fences projecting south and west.

- 40.048** The 1/4 section corner of sections 16 and 17, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, projecting 8 inches above ground, with the original sandstone, 12x10x5 inches deposited alongside, with a 3 inch threaded galvanized cap marked:

1958
UTE TRIBAL LAND
17 1/4 16

Added the marks, BLM 2004, to the cap.

N. 0° 04.5' E., beginning new measurement.

- 20.055** The N 1/16 section corner of sections 16 and 17, monumented with a galvanized iron pipe, 2 1/2 inches diameter, set in concrete, projecting 10 inches above ground, with the original sandstone, 8x6x6 inches deposited alongside, with a 3 inch threaded galvanized cap marked:

1958
1/16
UTE TRIBAL LAND

Added the marks, BLM 2004, to the cap.

Corner is located on a sagebrush flat, about 227 links east of a gravel road, bears northwest and southeast. Also, the corner is on the west side of a small draw, drains southwest.

N. 0° 31.2' W., beginning new measurement.

- 19.886** Point for the corner of sections 8, 9, 16 and 17, at proportionate distance, falls 19.7 links north of the centerline of Utah State Highway No. 121, there is no remaining evidence of the original corner.

Set a railroad spike flush with the surface of the highway.

From which

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 62° 06.0' E., 45.3 links distance, with aluminum cap marked: RM T1S R1E S9 29.9 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 11.4 links north of the north guardrail.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 47° 52.2' E., 92.3 links distance, with aluminum cap marked: RM T1S R1E S16 60.9 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 10.0 links south of the south guardrail.

From the corner of sections 9, 10, 15 and 16.

N. 89° 59.6' W., between sections 9 and 16.

19.950

Point for the E 1/16 section corner of sections 9 and 16, at proportionate distance, falls on the north shoulder and 25.8 links north of the centerline of Utah State Highway No. 121, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S9
E 1/16 ———
S16
2004

Set a 5 ft. steel fence post alongside the aluminum post.

39.900

Point for the 1/4 section corner of sections 9 and 16, at proportionate distance, falls on the north shoulder and 24.2 links north of the centerline of Utah State Highway No. 121, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
S9
1/4 ———
S16
2004

Set a 5 ft. steel fence post alongside the aluminum post.

From this corner, a 5/8 inch rebar with an orange cap marked: RMS UT PLS 161259, bears N. 3° 47.5 W. 25.2 links distance, located in north right-of-way fence, not used in this survey.

59.850

Point for the W 1/16 section corner of sections 9 and 16, at proportionate distance, falls on the north shoulder of Utah State Highway No. 121, 20.8 links north of the center line, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S9
W 1/16 ———
S16
2004

Set a 5 ft. steel fence post alongside the aluminum post.

79.800

The corner of sections 8, 9, 16 and 17.

N. 0° 48.3' E., between sections 8 and 9.

19.887

Point for the S 1/16 section corner of sections 8 and 9, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S 1/16
S8 | S9
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Fence corner bears N. 84° 30.0 E. 51.5 links distance, with fences projecting north and east.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 22.7 links east of a draw, 3 ft. wide, 3 ft. deep, drains southerly.

From this corner, a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 14 inches above ground, bears N. 84° 22.7' E., 48.9 links distance, with a 3 inch threaded galvanized cap marked:

1959
1/16

Added the marks, AM BLM 2004, to the cap.

This corner was not used in the course of this survey.

The galvanized pipe is located 1.7 links southwest of fence corner, with fences projecting north and east.

39.774

The 1/4 section corner of sections 8 and 9, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with the original sandstone, 8x8x8 inches above ground, marked 1/4, deposited alongside, with a 3 inch threaded galvanized cap marked:

UTE 1958
TRIBAL 1/4
LAND 8|9

Added the marks, BLM 2004, to the cap.

Corner is located on north side of a fence corner, with fences projecting north, south, east and west.

From the corner of sections 5, 6, 31 and 32, on the south boundary of the township, hereinbefore described.

N. 0° 11.9' E., between sections 31 and 32.

19.978

Point for the S 1/16 section corner of sections 31 and 32, at proportionate distance, falls in north and south paved road, there is no remaining evidence of the original corner.

Set a PK nail flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 84° 24.7' E., 49.0 links distance, with aluminum cap marked: RM S 1/16 S32 32.3 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

reference monument, bears S. 77° 49.4' W., 47.6 links distance, with aluminum cap marked: RM S 1/16 S31 31.4 FT 2004, with arrow pointing to the corner.

39.956

The 1/4 section corner of sections 31 and 32, monumented with a 5/8 inch rebar, flush with the paved road. This rebar is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 40° 38.5' W., 71.4 links distance, with aluminum cap marked: RM T1S R1E 1/4 S31 47.1 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 41° 48.5' W., 69.7 links distance, with aluminum cap marked: RM T1S R1E 1/4 S31 46.0 FT 2004, with arrow pointing to the corner.

N. 0° 17.4' E., beginning new measurement.

20.001

Point for the N 1/16 section corner of sections 31 and 32, at proportionate distance falls on the west side of a north and south paved highway, there is no remaining evidence of the original corner.

Set a PK nail flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 40° 27.1' E., 75.0 links distance, with aluminum cap marked: RM N 1/16 S32 49.25 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 32° 32.4' W., 82.9 links distance, with aluminum cap marked: RM N 1/16 S31 54.71 FT 2004, with arrow pointing to the corner.

40.002

The corner of sections 29, 30, 31 and 32, monumented with a rebar with a battered cap, at the intersection of roads. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $54^{\circ} 17.1'$ E., 59.7 links distance, with aluminum cap marked: RM T1S R1E S32 39.4 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears S. $44^{\circ} 59.9'$ W., 69.6 links distance, with aluminum cap marked: RM T1S R1E S31 45.9 FT 2004, with arrow pointing to the corner.

From this corner, the corner of sections 25, 30, 31 and 36, on the Uintah Special Meridian, bears N. $89^{\circ} 59.5'$ W., 80.446 chains distance, falls at the intersection of paved roads monumented with a railroad spike, 5 inches below the surface of the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $49^{\circ} 42.9'$ E., 74.2 links distance, with aluminum cap marked: RM T1S R1E S31 49.0 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $38^{\circ} 50.8'$ W., 83.0 links distance, with aluminum cap marked: RM T1S R1E S36 54.8 FT 2004, with arrow pointing to the corner.

From the corner of sections 28, 29, 32 and 33.

S. $89^{\circ} 55.9'$ W., between sections 29 and 32.

19.852

Point for the E 1/16 section corner of sections 29 and 32, at proportionate distance, falls on the north edge of a paved road. There is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $68^{\circ} 51.4'$ E., 49.6 links distance, with aluminum cap marked: RM T1S R1E E 1/16 S29 32.7 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Reference monument is located on north side of road, 1 link south of an east and west fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 53° 37.4' E., 60.4 links distance, with aluminum cap marked: RM T1S R1E E 1/16 S32 39.9 FT 2004, with arrow pointing to the corner.

Reference monument is located on south side of road, 2.3 links north of an east and west fence line.

39.704

The 1/4 section corner of sections 29 and 32, monumented with a 5/8 inch rebar, six inches below the surface of an east and west paved road, with a paved road bearing south and a dirt road bearing north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 52° 17.7' E., 49.6 links distance, with aluminum cap marked: RM T1S R1E 1/4 S29 32.7 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 52° 58.5' E., 55.9 links distance, with aluminum cap marked: RM T1S R1E 1/4 S32 36.9 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

N. 89° 54.8' W., beginning new measurement.

19.914

Point for the W 1/16 section corner of sections 29 and 32, at proportionate distance, falls in the center of an east and west paved road, with dirt road bearing north, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears S. 60° 55.1' W., 56.6 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S32 37.4 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Reference monument is located 1.5 links north of an east and west fence line on south side of paved road.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 53° 17.3' W., 61.1 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S29 40.3 FT 2004, with arrow pointing to the corner.

Reference monument is located 1.5 links south of an east and west fence line on north side of paved road.

39.828 The corner of sections 29, 30, 31 and 32.

N. 0° 21.2' W., between sections 29 and 30.

20.062 Point for the S 1/16 section corner of sections 29 and 30, at proportionate distance, falls in centerline of a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 41° 57.3' E., 70.0 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S29 46.2 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post in the east right-of-way fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 28 inches in the ground, with a magnet at base, for a reference monument, bears N. 53° 40.8' W., 55.2 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S30 36.5 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post in the west right-of-way fence line.

40.124 Point for the 1/4 section corner of sections 29 and 30, at proportionate distance, falls in north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

reference monument, bears S. $69^{\circ} 45.5'$ W., 50.4 links
distance, with aluminum cap marked: RM T1S R1E 1/4 S30 33.3
FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter,
set 24 inches in the ground, with a magnet at base, for a
reference monument, bears N. $48^{\circ} 45.2'$ W., 60.6 links
distance, with aluminum cap marked: RM T1S R1E 1/4 S30 40.0
FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

60.186

Point for the N 1/16 section corner of sections 29 and 30, at
proportionate distance, falls on west side of a north and south
paved road, in alignment with fences that project east and west,
there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter,
set 24 inches in the ground, with a magnet at base, for a
reference monument, bears N. $67^{\circ} 29.2'$ E., 59.6 links
distance, with aluminum cap marked: RM T1S R1E N1/16 S29
39.3 FT 2004, with arrow pointing to the corner.

Reference monument is located on the east side of a north
and south right-of-way fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter,
set 24 inches in the ground, with a magnet at base, for a
reference monument, bears S. $60^{\circ} 19.2'$ E., 63.1 links
distance, with aluminum cap marked: RM T1S R1E N1/16 S29
41.7 FT 2004, with arrow pointing to the corner.

Reference monument is located on the east side of a north
and south right-of-way fence line.

80.248

Point for the corner of sections 19, 20, 29 and 30, at
proportionate distance, falls in the south bound lane of a north
and south paved road, and in line with a road to the west, there
is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter,
set 24 inches in the ground, with a magnet at base, for a
reference monument, bears S. $65^{\circ} 18.0'$ E., 55.9 links

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

distance, with aluminum cap marked: RM T1S R1E S29 36.9 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 51° 42.0' W., 51.0 links distance, with aluminum cap marked: RM T1S R1E S30 33.7 FT 2004, with arrow pointing to the corner.

From this corner, the corner of sections 19, 24, 25 and 30, on the Uintah Special Meridian, bears S. 89° 57.4' W., 80.126 chains distance, monumented with a railroad spike, falls on the west edge of paved roads that bear north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 48° 54.9' E., 66.5 links distance, with aluminum cap marked: RM T1S R1E S19 43.9 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 51° 04.2' W., 66.4 links distance, with aluminum cap marked: RM T1S R1W S24 43.8 FT 2004, with arrow pointing to the corner.

From the corner of sections 20, 21, 28 and 29.

N. 89° 58.9' W., between sections 20 and 29.

19.927

Point for the E 1/16 section corner of sections 20 and 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S20
E 1/16 ———
S29
2004

Set a 5 ft. steel fence post alongside the aluminum post.

From this corner, a fence corner bears S. 76° 47' E., 53.0 links distance.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS**39.854**

Point for the 1/4 section corner of sections 20 and 29, at proportionate distance, falls on the south side of a gravel road that bears west and the west side of a gravel road that bears south, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 19° 15.0' W., 50.9 links distance, with aluminum cap marked: RM T1S R1E 1/4 S29 33.6 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 44° 45.8' E., 55.3 links distance, with aluminum cap marked: RM T1S R1E 1/4 S20 36.5 FT 2004, with arrow pointing to the corner.

From the spike in the road, a fence corner with fences projecting east, west and north, bears N. 21° 06' E., 45.5 links distance.

59.781

Point for the W 1/16 section corner of sections 20 and 29, at proportionate distance, falls on the south side of a gravel road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S20
W 1/16 ———
S29
2004

Set a 5 ft. steel fence post alongside the aluminum post.

From this corner,

Power pole No. R09447, bears North, 44.1 links distance.

Power pole No. R09448, S. 20° E., 6.2 links distance.

79.708

The corner of sections 19, 20, 29 and 30.

N. 0° 05.2' W., between sections 19 and 20.

20.061

Point for the S 1/16 section corner of sections 19 and 20, at proportionate distance, falls in the center of a north and south

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

paved road, and in line with fences projecting east and west, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 42° 12.5' E., 78.1 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S20 51.6 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 50° 09.4' W., 72.4 links distance, with aluminum cap marked: RM T1S R1E S 1/16 S19 47.8 FT 2004, with arrow pointing to the corner.

Both corners are located in a right-of-way fence on north side of paved road.

40.122

The 1/4 section corner of sections 19 and 20, monumented with a 1 inch bolt flush with the north and south paved road. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

A cross on a concrete head wall bears N. 84° 22.9' E., 72.7 links distance.

Power pole No. R09411, with a nail in it, bears S. 85° W., 47.3 links distance.

N. 0° 04.6' E., beginning new measurement.

20.010

Point for the N 1/16 section corner of sections 19 and 20, at proportionate distance, falls on west edge of a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 25° 46.8' W., 62.6 links distance, with aluminum cap marked: RM T1S R1E N1/16 S19 41.3 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 20 inches in the ground, with a magnet at base, for a reference monument, bears N. $28^{\circ} 59.7'$ W., 62.1 links distance, with aluminum cap marked: RM T1S R1E N1/16 S19 41.0 FT 2004, with arrow pointing to the corner.

Both Reference monuments are located in a right-of-way fence on west side of paved road.

40.020

The corner of sections 17, 18, 19 and 20, monumented with a drive gear flush with the intersection of paved roads, bearing north, south, east and west. This gear is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the corner.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $39^{\circ} 22.2'$ E., 75.1 links distance, with aluminum cap marked: RM T1S R1E S17 49.6 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $39^{\circ} 57.9'$ W., 76.7 links distance, with aluminum cap marked: RM T1S R1E S18 50.6 FT 2004, with arrow pointing to the corner.

From this corner, the corner of sections 13, 18, 19 and 24, on the Uintah Special Meridian, bears N. $89^{\circ} 58.4'$ W., 80.259 chains distance, monumented with a railroad spike on west edge of a north-south paved road, in alignment with a gravel road to the east and a dirt road to the west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $38^{\circ} 40.7'$ E., 68.5 links distance, with aluminum cap marked: RM T1S R1E S18 45.2 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 20 inches in the ground, with a magnet at base, for a reference monument, bears S. $42^{\circ} 43.0'$ E., 70.9 links distance, with aluminum cap marked: RM T1S R1E S19 46.8 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From the corner of sections 16, 17, 20 and 21.

N. 89° 59.3' W., between sections 17 and 20.

20.008

Point for the E 1/16 section corner of sections 17 and 20, at proportionate distance, falls near the centerline, of an east and west dirt road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, flush with the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
S17
E 1/16 —————
S20
2004

A fence corner, with fences projecting east, west and north, bears N. 36° 34.5' W., 76.4 links distance.

40.016

Point for the 1/4 section corner of sections 17 and 20, at proportionate distance, falls in an east and west gravel road and in line with fences projecting north and south. There is no remaining evidence of the original corner.

Set a railroad spike flush with the gravel road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 51° 12.5' W., 50.5 links distance, with aluminum cap marked: RM T1S R1E 1/4 S20 33.3 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 49° 11.6' W., 110.0 links distance, with aluminum cap marked: RM T1S R1E 1/4 S17 72.6 FT 2004, with arrow pointing to the corner.

60.024

Point for the W 1/16 section corner of sections 17 and 20, at proportionate distance, falls in a north edge of an east and west paved road, 5.3 links east of the east edge of a bridge and 12.1 links west of a fence projecting south. There is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 49° 29.6' E., 80.2 links distance, with aluminum cap marked: RM T1S R1E W1/16 S17 52.9 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 49° 01.4' W., 75.9 links distance, with aluminum cap marked: RM T1S R1E W1/16 S17 50.1 FT 2004, with arrow pointing to the corner.

80.032 The corner of sections 17, 18, 19 and 20.

N. 0° 08.3' E., between sections 17 and 18.

20.062 Point for the S 1/16 section corner of sections 17 and 18, at proportionate distance, falls 21.2 links east of the centerline of a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 28 inches in the ground, with a magnet at base, for a reference monument, bears S. 31° 44.2' E., 58.2 links distance, with aluminum cap marked: RM T1S R1E S1/16 S17 38.4 FT 2004, with arrow pointing to the corner.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 54° 52.8' W., 92.1 links distance, with aluminum cap marked: RM T1S R1E S1/16 S18 60.8 FT 2004, with arrow pointing to the corner.

40.124 Point for the 1/4 section corner of sections 17 and 18, at proportionate distance, falls on east shoulder of a paved road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S18 | S17
2004

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, east of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 45.5 links east of centerline of paved road.

Corner is located 9 links west of the east right-of-way fence line.

60.186

Point for the N 1/16 section corner of sections 17 and 18, at proportionate distance, falls 5.2 links east of the east right-of-way fence, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
N 1/16
S18 | S17
2004

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

80.248

Point for the corner of sections 7, 8, 17 and 18, at proportionate distance, falls on east edge of a north and south paved road, and the south edge of an east and west paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 9° 41.0' E., 100.9 links distance, with aluminum cap marked: RM T1S R1E S8 66.6 FT 2004, with arrow pointing to the corner.

Reference monument is located at the right-of-way fence corner with fences projecting north and east.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 28° 07.0' E., 33.0 links distance, with aluminum cap marked: RM T1S R1E S17 21.8 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Reference monument is located in the north and south right-of-way fence line on east side of paved road.

From this corner, the corner of sections 7, 12, 13 and 18, on the Uintah Special Meridian, monumented with a railroad spike 2 inches below the paved surface, bears S. $89^{\circ} 58.6'$ W., 80.428 chains distance. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $33^{\circ} 07.4'$ E., 73.0 links distance, with aluminum cap marked: RM T1S R1W S18 48.2 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $33^{\circ} 32.1'$ W., 80.6 links distance, with aluminum cap marked: RM T1S R1W S13 53.2 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

From the corner of sections 8, 9, 16 and 17.

N. $89^{\circ} 48.2'$ W., between sections 8 and 17.

19.994

Point for the E 1/16 section corner of sections 8 and 17, at proportionate distance, falls in the north barrow pit of a east and west paved road, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bed rock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T1S R1E
S8
E 1/16 ———
S17
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 27.3 links north of the centerline of paved road.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 39.988** Point for the 1/4 section corner of sections 8 and 17, at proportionate distance, falls 9.9 links north of the centerline of an east and west paved road, there is no remaining evidence of the original corner.
- Set a railroad spike flush with the road.
- From which
- An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 5° 56.3' E., 42.1 links distance, with aluminum cap marked: RM T1S R1E S 1/4 S8 27.8 FT 2004, with arrow pointing to the corner.
- An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 5° 29.9' W., 50.3 links distance, with aluminum cap marked: RM T1S R1E N1/4 S17 33.2 FT 2004, with arrow pointing to the corner.
- 59.982** Point for the W 1/16 section corner of sections 8 and 17, at proportionate distance, 21.2 links south of the centerline of an east and west paved road, there is no remaining evidence of the original corner.
- Set a railroad spike flush with the road.
- From which
- An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 51° 52.5' E., 42.3 links distance, with aluminum cap marked: RM T1S R1E W 1/16 S17 27.9 FT 2004, with arrow pointing to the corner.
- An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 58° 57.6' W., 47.9 links distance, with aluminum cap marked: RM T1S R1E W1/16 S17 31.6 FT 2004, with arrow pointing to the corner.
- Set a 5 ft. steel fence post alongside the aluminum post.
- 79.976** The corner of sections 7, 8, 17 and 18.
-
- N. 0° 36.0' E., between sections 7 and 8.
- 20.063** Point for the S 1/16 section corner of sections 7 and 8, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

40.126 Point for the 1/4 section corner of sections 7 and 8, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
1/4
S7 | S8
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 37.9 links west of a north and south fence line, and 86.4 links east of centerline of paved road, bears south and curves to the northwest.

60.189 Point for the N 1/16 section corner of sections 7 and 8, at proportionate distance, there is no remaining evidence of the original corner, not monumented.

80.252 The corner of sections 5, 6, 7 and 8, monumented with an aluminum post, 2 1/2 inches diameter, projecting 6 inches above ground, in a stone collar, with aluminum cap marked as described in the official record of the 1998 dependent resurvey.

Dependent Resurvey of a Portion of the Subdivision of Section 16
by the Three Mile Method,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

Reestablishment of the Survey Executed by C.L. DuBois in 1875

From the center S 1/16 section corner of section 16, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 8 inches above ground, with the original sandstone, 15x10x5 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S16 1/16

Added the marks, BLM 2004, to the cap.

No other improvements were made at this corner.

S. 89° 43.8' W., on the E-W centerline of the S 1/2 of section 16.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 16
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS**18.954**

The SW 1/16 section corner of section 16, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 6 inches above ground, with the original sandstone, 10x8x6 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S16 1/16

Added the marks, BLM 2004, to the cap.

No other improvements were made at this corner.

N. 89° 43.5' W., beginning new measurement.

20.005

The S 1/16 section corner of sections 16 and 17.

From the center W 1/16 section corner of section 16, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 4 inches above ground, with the original sandstone, 8x5x5 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1958
UTE 1/16
TRIBAL
LAND

Added the marks, BLM 2004, to the cap.

No other improvements were made at this corner.

N. 89° 59.5' W., on the E-W centerline of section 16.

19.977

The 1/4 section corner of section 16 and 17.

From the NW 1/16 section corner of section 16, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 2 inches above ground, with the original sandstone, 12x12x6 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S16 1/16

Added the marks, BLM 2004, to the cap.

No other improvements were made at this corner.

Corner is located in a north and south fence line.

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 16
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

S. 88° 31.9' W., on the E-W centerline of the N 1/2 of section 16.

20.219 The N 1/16 section corner of sections 16 and 17.

Survey of the Subdivision of Section 16,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 16 and 21.

N. 0° 18.4' E., on the N-S centerline of section 16.

19.878 The center S 1/16 section corner of section 16.

From the W 1/16 section corner of sections 16 and 21.

N. 1° 37.9' E., on the N-S centerline of the W 1/2 of section 16.

19.866 The SW 1/16 section corner of section 16.

N. 0° 09.2' W., beginning new measurement.

20.117 The center W 1/16 section corner of section 16.

N. 0° 43.8' E., beginning new measurement.

20.578 The NW 1/16 section corner of section 16.

N. 0° 14.3' W., beginning new measurement.

19.365 The W 1/16 section corner of sections 9 and 16.

Dependent Resurvey of the Subdivision of Section 17
by the Three Mile Method,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of section 16 and 17.

N. 89° 53.0' W., on the E-W centerline of the S 1/2 of section 17.

19.933 The SE 1/16 section corner of sections 17, monumented with a sandstone, 16x9x7 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

**DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 17
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
SE 1/16 S17
2004

Corner is located in an east and west fence line, 74.9 links east of a fence corner, with fences projecting east, west and south.

N. 89° 45.0' W., beginning new measurement.

20.061

The center S 1/16 section corner of section 17, at the corner of old cedar post fences projecting east, west and south, and a new T-post fence projecting north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S17
C
2004

Raise a mound of stone, 2 ft. base, 1 ft. high, west of the aluminum post.

S. 89° 47.0' W., beginning new measurement.

19.902

The SW 1/16 section corner of section 17, at the corner of fences projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16 | S17
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 18.2 links east of a 4 ft. wide, 3 ft. deep, ditch that flows south.

N. 89° 59.9' W., beginning new measurement.

20.059 The S 1/16 section corner of sections 17 and 18.

From the 1/4 section corner of sections 16 and 17.

N. 89° 32.5' W., on the E-W centerline of section 17.

19.981 The center E 1/16 section corner of section 17, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set in concrete, projecting 2 inches above ground, with the original sandstone, 18x10x10 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1958
UTE TRIBAL LAND
1/16

Added the marks, BLM 2004, to the cap.

No other improvements were made at this corner.

A small mound of stone is located to the south of pipe.

Corner is located in large sagebrush flat about 5.30 chains northwest of oil well tanks and buildings.

S. 89° 31.4' W., beginning new measurement.

9.969 Point for the center W-E 1/64 section corner of section 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-W-E 1/64
S17
2004

Corner is located in an east and west fence line, 6.1 links west of corner of fences, projecting north and west.

19.938 The center 1/4 section corner of section 17, at the corner of fences, projecting east, west and south. This position is harmoniously related to other identified original corners in the

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4 S17
2004

Rebuild a mound of stone, 2 ft. base, 1 ft. high, west of the aluminum post.

S. 89° 54.3' W., beginning new measurement.

9.997 Point for the center E-W 1/64 section corner of section 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-E-W 1/64
S17
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 6.1 links south of an east and west fence line in thick brush.

19.994 The center W 1/16 section corner of sections 17, at the corner of fences, projecting west and south. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W 1/16
C—C
S17
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 9.1 links east of a ditch, 3 ft. wide, 2 ft. deep, flows south.

N. 89° 37.5' W., beginning new measurement.

19.964 The 1/4 section corner of section 17 and 18.

From the N 1/16 section corner of sections 16 and 17.

N. 89° 45.3' W., on the E-W centerline of the N 1/2 of section 17.

19.946 The NE 1/16 section corner of section 17, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set in concrete, projecting 8 inches above ground, with the original sandstone, 15x11x8 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1958
UTE TRIBAL LAND
1/16

Added the marks, BLM 2004, to the cap.

A small mound of stone, 3 ft. base, 1 1/2 ft. high, is located south of the corner.

Corner is located on large sagebrush flat.

N. 89° 59.2' W., beginning new measurement.

9.984 Point for the center W-NE 1/64 section corner of section 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-W-NE 1/64
S17
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on north edge of thick brush.

19.968 Point for the center N 1/16 section corner of section 17, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
N 1/16 | S17
C
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 42.4 links north of an east and west fence line and 37.9 links east of a canal, 10 ft. wide and 5 ft. deep.

29.952 Point for the center E-NW 1/64 section corner of section 17.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
C-E-NW 1/64
S17
2004

Set a 5 ft. steel fence post alongside the aluminum post.

A fence corner, bears S. 15° 07' E., 58.2 links distance, with fences projecting east, west and south.

39.936 Point for the NW 1/16 section corner of section 17, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T1S R1E
NW 1/16
S17
2004

A fence corner, bears S. 14° 17.5' W., 79 links distance, with fences projecting east, west and north.

59.904 The N 1/16 section corner of sections 17 and 18.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 17
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Survey of the Subdivision of Section 17
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the SE 1/16 section corner of section 17.

N. 0° 12.9' W., on the N-S centerline of the E 1/2 of section 17.

20.143 The center E 1/16 section corner of section 17.

N. 0° 10.2' E., beginning new measurement.

19.980 The NE 1/16 section corner of section 17.

N. 0° 22.7' E., beginning new measurement.

19.870 The E 1/16 section corner of sections 8 and 17.

From the center W-E 1/64 section corner of section 17.

N. 0° 07.5' E., on the N-S centerline of the SW 1/4 of the NE 1/4 of section 17.

20.066 The center W-NE 1/64 section corner of section 17.

From the center S 1/16 section corner of section 17.

N. 0° 08.1' E., on the N-S centerline of section 17.

19.890 The center 1/4 of section 17.

From the center N 1/16 section corner of section 17.

N. 0° 17.9' E., on the N-S centerline of section 17.

19.934 The 1/4 section corner of sections 8 and 17.

From the center E-W 1/64 section corner of section 17.

N. 0° 06.9' E., on the N-S centerline of the SE 1/4 of the NW 1/4 of section 17.

20.170 The center E-NW 1/64 section corner of section 17.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20
BY THE THREE MILE METHOD
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

Dependent Resurvey of the Subdivision of Section 20
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of section 20 and 21.

N. 89° 57.7' W., on the E-W centerline of the S 1/2 of section 20.

19.893

The SE 1/16 section corner of section 20, monumented with a sandstone, 18x8x6 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S20
2004

Deposit the marked stone alongside the aluminum post.

N. 89° 59.1' W., beginning new measurement.

19.965

Point for the center S 1/16 section corner of section 20, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S1/16 | S20
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 41 links west of a fence corner with fences projecting east and north, on a northeast slope, with a pond approximately 3.00 chains north.

39.930

Point for the SW 1/16 section corner of section 20, at proportionate distance, there is no remaining evidence of the original corner.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16
S20
2004

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the aluminum post.

Set a wood post on east side of the aluminum post.

A fence corner, bears N. 67° 45.6' E., 20.0 links distance, with fences projecting north, south, east and west.

59.895 The S 1/16 section corner of sections 19 and 20.

From the 1/4 section corner of sections 20 and 21.

N. 89° 31.4' W., on the E-W centerline of section 20.

19.969 The center E 1/16 section corner of section 20, monumented with a sandstone, 15x9x6 inches, dimly marked, 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C——C
S20
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the aluminum post.

Corner is located on a sagebrush flat at the edge of a tree line, bears northwest and southeast.

S. 89° 36.7' W., beginning new measurement.

19.877 The center 1/4 section corner of section 20, monumented with a sandstone, 12x9x6 inches, dimly marked, 1/4 on north fence.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4 S20
2004

Deposit the marked stone alongside the aluminum post.

Corner is located at a fence corner, with fences projecting east, west and south, also 61 links east of a fence projecting north.

N. 89° 39.2' W., beginning new measurement.

19.992

Point for the center W 1/16 section corner of section 20, determined latitudinally, by a fence line extending east and west and longitudinally by proportionate measurement.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W 1/16
C — C
S20
2004

S. 89° 44.5' W., beginning new measurement.

19.992

The 1/4 section corner of sections 19 and 20.

From the N 1/16 section corner of sections 20 and 21.

N. 89° 55.2' W., on the E-W centerline of the N 1/2 of section 20.

20.139

The NE 1/16 section corner of section 20, monumented with a sandstone, 18x8x7 inches, plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
NE 1/16
S20
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Located at the corner of fences projecting north and east.

N. 88° 59.1' W., beginning new measurement.

20.200

The center N 1/16 section corner of section 20, monumented with a sandstone, 12x8x6 inches, with no visible marks, at the corner of fences that projects north, south and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a collar of stone, with aluminum cap marked:

T1S R1E
C
N 1/16 | S20
C
2004

Deposit the unmarked stone alongside the aluminum post.

S. 89° 29.5' W., beginning new measurement.

19.814

Point for the NW 1/16 section corner of section 20, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16 S20
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 20
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located in an east and west fence line, 35 links west of a fence corner with fences projecting east, west, north and south.

39.628

The N 1/16 section corner of sections 19 and 20.

Survey of the Subdivision of Section 20
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the E 1/16 section corner of sections 20 and 29.

N. 0° 15.1' E., on the N-S centerline of the E 1/2 of section 20.

20.065

The SE 1/16 section corner of section 20.

N. 0° 10.6' W., beginning new measurement.

20.181

The center E 1/16 section corner of section 20.

N. 0° 01.0' W., beginning new measurement.

19.900

The NE 1/16 section corner of section 20.

N. 0° 39.5' E., beginning new measurement.

20.008

The E 1/16 section corner of section 17 and 20.

From the center S 1/16 section corner of section 20.

N. 0° 04.3' E., on the N-S centerline of section 20.

20.041

The center 1/4 section corner of section 20.

N. 0° 55.2' W., beginning new measurement.

20.396

The center N 1/16 section corner of section 20.

N. 1° 13.1' E., beginning new measurement.

19.656

The 1/4 section corner of sections 17 and 20.

From the SW 1/16 section corner of section 20.

N. 0° 00.6' W., on the N-S centerline of the W 1/2 of section 20.

**SURVEY OF THE SUBDIVISION OF SECTION 20
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS**20.157**

The center W 1/16 section corner of section 20.

From the NW 1/16 section corner of section 20.

N. 0° 38.5' E., on the N-S centerline of the W 1/2 of section 20.

19.832

The W 1/16 section corner of sections 17 and 20.

Dependent Resurvey of the Subdivision of Section 21
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 21 and 22.

N. 89° 31.7' W., on the E-W centerline of the S 1/2 of section 21.

20.197

The SE 1/16 section corner of section 21, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set in concrete, projecting 8 inches above ground, with the original sandstone, 17x10x8 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
S21 1/16

Added the marks, BLM 2004, to the cap.

Located in a north and south fence line.

N. 89° 56.8' W., beginning new measurement.

19.995

Point for the center S 1/16 section corner of section 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S21
C
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Corner is located on east bank of wash, drains south.

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 21
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

39.990

The SW 1/16 section corner of section 21, monumented with a sandstone, 13x11x11 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16
S21
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

S. 89° 55.9' W., beginning new measurement.

20.007

The S 1/16 section corner of sections 20 and 21.

From the 1/4 section corner of sections 21 and 22.

S. 89° 57.4' W., on the E-W centerline of section 21.

20.137

The center E 1/16 section corner of section 21, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set in concrete, projecting 8 inches above ground, with the original sandstone, 18x10x9 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

S21 1/16
1959

Added the marks, BLM 2004, to the cap.

Corner is located in an east and west fence line, and 1.5 links west of a fence corner with fences projecting east, west and south.

From this corner, U.S. Geological Survey Triangulation Station "SUNDANCE", , bears S. 40° 11.6' W., 0.459 chains distance, monumented with a standard cap on the top of a 12 inch high concrete block.

N. 89° 42.2' W., beginning new measurement.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 21
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

21.018 The center 1/4 section corner of section 21, at the corner of old fences projecting east, west and north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4
S21
2004

Corner is located on south side of wood fence post, about 100 links east of a drainage, drains south.

N. 89° 54.6' W., beginning new measurement.

19.512 Point for the center W 1/16 section corner of section 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W 1/16
C ——— C
S21
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on a north side of a small hill.

39.024 The 1/4 section corner of sections 20 and 21.

From the N 1/16 section corner of sections 21 and 22.

N.89° 02.4' W., on the E-W centerline of the N 1/2 section of section 21.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 21
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS**19.722**

The NE 1/16 section corner of section 21 determined latitudinally on line and longitudinally at record distance, 96 links east of a wash, 15 links wide, drains south, there is no remaining evidence of the original monument.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S21
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 22.7 links south of the centerline of a graveled road, bears east and west, 39.4 links north of an east and west fence line, and 54.5 links south of an east and west fence line.

41.116

The center N 1/16 section corner of section 21, at the corner of fences projecting north, south and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
N1/16 | S21
C
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, east of the corner.

Corner is located on east side of wood fence corner, and about 100 links west of a drainage, drains south.

S. 88° 08.9' W., beginning new measurement.

18.812

The NW 1/16 of section corner of section 21, at the corner of fences projecting west and north. This position is harmoniously related to other identified original corners in the area, and is

**SURVEY OF THE SUBDIVISION OF SECTION 21
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S21
2004

Corner is located on the southeast side of the wood fence corner.

N. 89° 49.7' W., beginning new measurement.

20.100 The N 1/16 section corner of sections 20 and 21.

Survey of the Subdivision of Section 21
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the E 1/16 section corner of sections 21 and 28.

N. 0° 37.8' W., on the N-S centerline of the E 1/2 section of section 21.

20.002 The SE 1/16 section corner of section 21.

N. 0° 10.7' E., beginning new measurement.

19.872 The center E 1/16 section corner of section 21.

From the center 1/4 section corner of section 21.

N. 0° 07.7' E., on the N-S centerline of section 21.

20.648 The center N 1/16 section corner of section 21.

N. 0° 05.3' E., beginning new measurement.

19.621 The 1/4 section corner of sections 16 and 21.

From the center W 1/16 section corner of section 21.

N. 2° 09.7' E., on the N-S centerline of the W 1/2 of section 21.

20.023 The NW 1/16 section corner of section 21.

**SURVEY OF THE SUBDIVISION OF SECTION 21
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. $1^{\circ} 39.4'$ W., beginning new measurement.

20.167 The W $1/16$ section corner of sections 16 and 21.

Dependent Resurvey of the Subdivision of Sections 25
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S $1/16$ section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.

S. $89^{\circ} 58.3'$ W., on the E-W centerline of the S $1/2$ of section 25.

19.837 Point for the SE $1/16$ section corner of section 25, at the corner of fences, projecting east, west and north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE $1/16$
S25
2004

Corner is located on the south side of the fence corner.

S. $89^{\circ} 40.6'$ W., beginning new measurement.

9.950 Point for the center W-SE $1/64$ section corner of section 25, not monumented.

19.900 Point for the center S $1/16$ section corner of section 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R1E
C
S1/16 | S25
C
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 25
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 29 links west of a canal that drains south, 3 links north of an east and west fence line, and 44 links west of the corner of fences projecting east, west and north.

39.800

The SW 1/16 section corner of section 25, monumented with a sandstone, 15x12x5 inches, marks have been obliterated.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16
S25
2004

Located at the corner of fences projecting north, south and east.

N. 89° 19.9' W., beginning new measurement.

20.024

The S 1/16 section corner of sections 25 and 26.

From the 1/4 section corner of sections 25 and 30, on the east boundary of the township, hereinbefore described.

S. 89° 46.8' W., on the E-W centerline of section 25.

19.988

Point for the center E 1/16 section corner of section 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E1/16
C ——— C
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on east side of Deep Creek, 2.3 links north of a east and west fence line, and 3 links west of a fence that projects south.

The fences were not used in the course of this survey because they wander around the creek.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 25
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

39.976 Point for the center 1/4 section corner of section 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C1/4
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 23 links south of a canal that flows east, 11 links north of a ditch, and in line with a fence that projects south.

59.964 Point for the center W 1/16 section corner of section 25, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W1/16
C——C
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located under power lines, 6.5 links from power pole No. 533, and 7.6 links west of a north and south fence line.

79.952 The 1/4 section corner of sections 25 and 26.

From the N 1/16 section corner of section 25 and 30, on the east boundary of the township, hereinbefore described.

N. 89° 43.6' W., on the E-W centerline of the N 1/2 section 25.

20.008 The NE 1/16 section corner of section 25, at the corner of old fences projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 25
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S25
2004

Corner is located on east side of fence post.

S. 89° 53.4' W., beginning new measurement.

- 19.753** Point selected for the witness corner to the center N 1/16 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

WC
T1S R1E
C
← C-N 1/16 | S25
C
2004

- 20.043** True point for the center N 1/16 section corner of section 25, determined latitudinally by an east and west fence line and longitudinally, at proportionate distance, falls in a canal that flows southeasterly.
-

S. 89° 48.3' W., beginning new measurement.

- 20.043** The NW 1/16 section corner of section 25, at the corner of fences, projecting east, west and north. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
NW1/16
S25
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 25
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. 89° 44.7' W., beginning new measurement.

20.122 The N 1/16 section corner of sections 25 and 26.

Survey of the Subdivision of Section 25
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the E 1/16 section corner of sections 25 and 36.

N. 0° 07.7' E., on the N-S centerline of the E 1/2 section 25.

4.990 Point for the center S-S-SE 1/256 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-S-S-SE 1/256
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

19.960 The SE 1/16 section corner of section 25.

From the W-E 1/64 section corner of sections 25 and 36.

N. 0° 02.8' E., on the N-S centerline of the SW 1/4 of the SE 1/4 of section 25.

4.975 Point for the center S-SW-SE 1/256 section corner of section 25.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-S-SW-SE 1/256
S25
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in a horse pasture.

19.900 The point for the center W-SE 1/64 section corner of section 25.

From the center S-S-SE 1/256 section corner of section 25.

**SURVEY OF THE SUBDIVISION OF SECTION 25
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

S. 89° 55.2' W., on the E-W centerline of the SE 1/4 of the SW 1/4 of the SE 1/4 of section 25.

9.929 The center S-SW-SE 1/256 section corner of section 25.

Dependent Resurvey of the Subdivision of Section 26
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 25 and 26.

S. 89° 46.7' W., on the E-W centerline of the S 1/2 of section 26.

19.984 Point for the SE 1/16 section corner of section 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE1/16
S26
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is set in a north and south fence line.

39.968 Point for the center S 1/16 section corner of section 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S26
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 16.7 links east of a new north and south fence line.

59.952 The SW 1/16 section corner of section 26, determined at the intersection of the extension of fences from the south and west,

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 26
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

falls in a dirt road. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set a railroad spike flush with the dirt road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears S. 2° 28.5' E., 39.4 links distance, with aluminum cap marked: RM T1S R1E SW 1/16 S26 26.0 FT 2004, with arrow pointing to the corner.

Reference monument is located in the south fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, for a reference monument, bears N. 87° 11.5' W., 34.2 links distance, with aluminum cap marked: RM T1S R1E SW 1/16 S26 22.6 FT 2004, with arrow pointing to the corner.

Reference monument is located in the west fence line.

S. 89° 19.4' W., beginning new measurement.

20.062 The S 1/16 section corner of sections 26 and 27.

From the 1/4 section corner of sections 25 and 26.

S. 89° 56.6' W., on the E-W centerline of section 26.

19.984 The center E 1/16 section corner of section 26, at the corner of fences, projecting north, south and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E1/16
C — C
S26
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 26
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located on west side of wood fence post.

Survey of the Subdivision of Sections 26
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the E 1/16 section corner of sections 26 and 35.

N. 0° 26.7' W., on the N-S centerline of the E 1/2 of section 26.

19.980 The SE 1/16 section corner of section 26.

N. 0° 43.4' W., beginning new measurement.

20.022 The center E 1/16 section corner of section 26.

Dependent Resurvey of the Subdivision of Section 27
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 26 and 27.

N. 89° 40.0' W., on the E-W centerline of the S 1/2 section 27.

10.020 Point for the center E-SE 1/64 section corner of section 27, not monumented.

20.040 Point for the SE 1/16 section corner of section 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S27
2004

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

30.060 Point for the center W-SE 1/64 section corner of section 27.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27
BY THE THREE MILE METHOD
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, in a collar of stone, with aluminum cap marked:

T1S R1E
C-W-SE 1/64
S27
2004

Set a 5 ft. steel fence post alongside the aluminum post.

40.080

Point for the center S 1/16 section corner of section 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 30 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | 1/64
C
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, east of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on east edge of an oil line.

50.100

Point for the center E-SW 1/64 section corner of section 27.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-E-SW 1/64
S27
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 11.4 links west of a culvert in a ditch and 12.9 links east of a fence corner with fences projecting south and west.

60.120

The SW 1/16 section corner of sections 27, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

19 inches above ground, with a 3 inch threaded galvanized cap marked:

1959
1/16
S27

This position is harmoniously related to other identified original corners in the area and is accepted as the best available evidence of the original corner.

Added the marks, BLM 2004, to the cap.

N. 89° 17.6' W., beginning new measurement.

19.954 The S 1/16 section corner of sections 27 and 28.

From the 1/4 section corner of sections 26 and 27.

N. 88° 36.4' W., on the E-W centerline of section 27.

20.240 The center E 1/16 section corner of section 27, monumented with a sandstone, 16x10x8 inches, firmly set and plainly marked 1/16 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C ——— C
S27
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 1 ft. high, west of the corner.

Set a 5 ft. steel fence post along the east side of the aluminum post.

Corner is located 4.6 links north of an east and west fence line.

N. 89° 59.8' W., beginning new measurement.

9.983 Point for the center W-E 1/64 section corner of section 27.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-W-E 1/64
S27
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in an east and west fence line.

19.966

The center 1/4 section corner of section 27, at the corner of fences, projecting north and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4
S27
2004

Raise a mound of stone, 4 ft. base, 2 ft. high, west of the corner.

Corner is located on the west side of a 5 inch diameter pipe used for the fence corner.

N. 89° 46.5' W., beginning new measurement.

19.935

The center W 1/16 section corner of section 27, monumented with a mound of stone with an old lathe in it. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point (center of mound)

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground to bedrock, with a magnet at base, and in a mound of stone, 4 ft. base to top of aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
W 1/16
C ——— C
S27
2004

Corner is located on an open sagebrush flat.

N. 88° 19.5' W., beginning new measurement.

20.102 The 1/4 section corner of sections 27 and 28.

From the N 1/16 section corner of section 26 and 27.

N. 88° 48.0' W., on the E-W centerline of the N 1/2 of section 27.

20.091 The NE 1/16 section corner of section 27, monumented with a sandstone, 16x10x10 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S27
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Corner is located in a sagebrush flat.

N. 89° 35.4' W., beginning new measurement.

20.065 Point for the center N 1/16 section corner of section 27, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, and in a collar of stone, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 27
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C
N 1/16 | S27
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 34.4 links N. 84° 19' W. from a fence corner with fences projecting south and west.

40.130

The NW 1/16 section corner of section 27, monumented with a sandstone, 13x12x8 inches, plainly marked 1/16 on north face, and a mound of stone is north of the sandstone.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, and in a collar of stone, with aluminum cap marked:

T1S R1E
NW 1/16
S27
2004

Deposit the marked stone alongside the aluminum post.

N. 88° 33.3' W., beginning new measurement.

19.996

The N 1/16 section corner of sections 27 and 28.

Survey of the Subdivision of Section 27
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the E-E 1/64 section corner of sections 27 and 34.

N. 0° 05.0' E., on the N-S centerline of the SE 1/4 of the SE 1/4 of section 27.

4.968

Point for the center S-SE-SE 1/256 section corner of section 27, falls on the north edge of a ditch.

Set a 5 ft. steel fence post 3 1/2 ft. in the ground at the corner point.

From which

**SURVEY OF THE SUBDIVISION OF SECTION 27
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 79° 23.5' W., 23.2 links distance, with aluminum cap marked: RM T1S R1E C-S-SE-SE 1/256 S27 15.3 FT 2004, with arrow pointing to the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

19.872 Point for the center E-SE 1/64 section corner of section 27.

From the S-S-S 1/256 section corner of sections 26 and 27.

N. 89° 37.8' W., on the E-W centerline of the SE 1/4 of the SE 1/4 of the SE 1/4 of section 27.

10.003 The center S-SE-SE 1/256 section corner of section 27.

From the center W-SE 1/64 section corner of section 27.

N. 0° 17.9' W., on the N-S centerline of the NW 1/4 of the SE 1/4 of section 27.

20.194 The center W-E 1/64 section corner of section 27.

From the center S 1/16 section corner of section 27.

N. 0° 12.1' W., on the N-S centerline of section 27.

20.139 The center 1/4 section corner of section 27.

N. 0° 17.1' E., beginning new measurement.

19.950 The center N 1/16 section corner of section 27.

From the E-W 1/64 section corner of sections 27 and 34.

N. 0° 10.9' W., on the N-S centerline of the SE 1/4 of the SW 1/4 of section 27.

19.838 The center E-SW 1/64 section corner of section 27.

Dependent Resurvey of the Subdivision of Section 28
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 27 and 28.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 28
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

S. 89° 47.8' W., on the E-W centerline of the S 1/2 of section 28.

20.007

Point for the SE 1/16 section corner of section 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S28
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

40.014

Point for the center S 1/16 section corner of section 28, determined latitudinally by an east and west fence line and longitudinally by proportionate distance, there is no remaining evidence of the original corner monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S28
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 43.9 links west of a fence corner with fences projecting north, south and west.

N. 89° 55.0' W., beginning new measurement.

20.007

The SW 1/16 section corner of section 28, monumented with a sandstone, 18x8x8 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 28
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
SW 1/16
S28
2004

Deposit the marked stone alongside the aluminum post.

Set a 6 ft. steel fence post alongside the aluminum post.

Corner is located at a fence corner with fences projecting east and north.

N. 89° 17.3' W., beginning new measurement.

19.879 The S 1/16 section corner of sections 28 and 29.

From the 1/4 section corner of sections 27 and 28.

S. 89° 35.2' W., on the E-W centerline of section 28.

19.918 Point for the center E 1/16 section corner of section 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C——C
S28
2004

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

39.836 The center 1/4 section corner of section 28, at the corner of fences, projecting south and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 28
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C 1/4
S28
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, northeast of the corner.

Corner is located on northeast side of fence corner.

S. 89° 45.2' W., beginning new measurement.

20.052

The center W 1/16 section corner of section 28, at the corner of fences, projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W 1/16
C——C
S28
2004

Corner is located on north side of fence corner.

N. 89° 38.4' W., beginning new measurement.

19.973

The 1/4 section corner of sections 28 and 29.

From the N 1/16 section corner of sections 27 and 28.

N. 89° 53.6' W., on the E-W centerline of the N 1/2 section 28.

19.873

The NE 1/16 section corner of section 28, monumented with a sandstone, 18x10x8 inches, firmly set and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 28
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
NE 1/16
S28
2004

Deposit the marked stone alongside the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

S. 89° 45.7' W., beginning new measurement.

20.103

Point for the center N 1/16 section corner of section 28, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
N 1/16 | S28
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

40.206

The NW 1/16 section corner of section 28, monumented with a sandstone, 18x10x9 inches, marked 1/16 on north face, located on northeast side of a wood fence corner with fences projecting south and west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S28
2004

Deposit the marked stone alongside the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

N. 89° 59.3' W., beginning new measurement.

19.923

The N 1/16 section corner of sections 28 and 29.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 28
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Survey of the Subdivision of Sections 28
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of sections 28 and 33.

N. 0° 30.6' W., on the N-S centerline of section 28.

19.778 The center S 1/16 section corner of section 28.

N. 0° 11.2' E., beginning new measurement.

20.296 The center 1/4 section corner of section 28.

From the SW 1/16 section corner of section 28.

N. 0° 03.4' E., on the N-S centerline of the W 1/2 section 28.

20.180 The center W 1/16 section corner of section 28.

N. 0° 21.0' W., beginning new measurement.

20.180 The NW 1/16 section corner of section 28.

N. 0° 14.3' E., beginning new measurement.

20.021 The W 1/16 section corner of sections 21 and 28.

Dependent Resurvey of the Subdivision of Section 29
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 28 and 29.

N. 89° 47.3' W., on the E-W centerline of the S 1/2 section 29.

19.920 The SE 1/16 section corner of section 29, at the corner of fences, projecting north, south and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S29
2004

S. 89° 56.7' W., beginning new measurement.

19.885

Point for the center S 1/16 section corner of section 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S29
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 22.7 links west of the centerline of a north and south gravel road, and 12.6 links east of a north and south fence line.

39.770

Point for the SW 1/16 section corner of section 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16
S29
2004

Corner is located 3 links west of a north and south fence line and 63.6 links north of a east and west fence line.

59.655

The S 1/16 section corner of sections 29 and 30.

From the 1/4 section corner of sections 28 and 29.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. 89° 55.2' W., on the E-W centerline of section 29.

19.932

Point for the center E 1/16 section corner of section 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C ——— C
S29
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Corner is located 8.3 links east of a fence line that projects and curves to the west around the hay field, and in line with a fence that projects west.

Corner falls on the northwest side of a hay field.

39.864

Point for the center 1/4 section corner of section 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4
S29
2004

Corner is located 21.2 links west of the centerline of a dirt road, bearing north and south and in line with fences that project to the west and to the east.

59.796

The center W 1/16 section corner of section 29, at the corner of fences, projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

T1S R1E
W 1/16
C——C
S29
2004

Corner is located northwest side of fence corner, and 15 links east of a 5 ft. wide, 4 ft. deep ditch, flows south.

S. 89° 49.0' W., beginning new measurement.

19.825 The 1/4 section corner of sections 28 and 29.

From the N 1/16 section corner of sections 28 and 29.

N. 89° 52.7' W., on the E-W centerline of the N 1/2 section 29.

19.932 Point for the NE 1/16 section corner of section 29, determined latitudinally by an east and west fence line and longitudinally by proportionate distance, there is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S29
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, south of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 7.5 links east of a fence corner with fences projecting east, west and N. 45° W.

N. 89° 58.9' W., beginning new measurement.

19.932 Point for the center N 1/16 section corner of section 29, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 29
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C
N 1/16 | S29
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in a north and south fence, 27.3 links west of the centerline of a north and south dirt road and 22.7 links north of fences projecting east and west.

39.864

Point for the NW 1/16 section corner of section 29, determined longitudinally by a north and south fence line, and latitudinally on line. There is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S29
2004

Corner is located 24.2 links north of a fence corner, with fences projecting north, south and east.

59.731

The N 1/16 section corner of sections 29 and 30.

Dependent Resurvey of the Subdivision of Section 32
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 32 and 33.

S. 89° 51.1' W., on the E-W centerline of the S 1/2 section 32.

19.778

The SE 1/16 section corner of section 32, at the corner of fences, projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 32
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
SE 1/16
S32
2004

Corner is located on northwest side of fence corner.

N. 89° 59.6' W., beginning new measurement.

19.995

Point for the center S 1/16 section corner of section 32, at proportionate distance, falls on the west edge of a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 42° 34.6' W., 27.9 links distance, with aluminum cap marked: RM T1S R1E C-S 1/16 S32 18.4 FT 2004, with arrow pointing to the corner.

Reference monument is located in the west right-of-way, north and south fence line.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 61° 31.0' W., 19.4 links distance, with aluminum cap marked: RM T1S R1E C-S 1/16 S32 12.8 FT 2004, with arrow pointing to the corner.

Reference monument is located in the west right-of-way, north and south fence line.

39.990

The SW 1/16 section corner of section 32, at the corner of fences, projecting north, south, east and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R1E
SW 1/16 S32
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 32
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

An unmarked sandstone, 18x12x8 inches, lying loose alongside fence corner, deposit the unmarked stone alongside the aluminum post.

N. 89° 52.5' W., beginning new measurement.

20.003

The S 1/16 section corner of sections 31 and 32.

From the 1/4 section corner of sections 32 and 33.

N. 89° 57.4' W., on the E-W centerline of section 32.

19.850

Point for the center E 1/16 section corner of section 32, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T1S R1E
E 1/16
C ——— C
S32
2004

Corner is located in an east and west fence line, 33.6 links west of a corner of fences projecting north, south, east and west.

39.700

Point for the center 1/4 section corner of section 32, at proportionate distance, falls on west edge of a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 16° 46.4' W., 12.1 links distance, with aluminum cap marked: RM T1S R1E C1/4 S32 8.0 FT 2004, with arrow pointing to the corner.

Reference monument is located 1.5 links east of a north and south right-of-way fence on the west side of paved road.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 26° 00.3' W., 9.6 links distance, with aluminum cap marked: RM T1S R1E C 1/4 S32 6.3 FT 2004, with arrow pointing to the corner.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 32
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Reference monument is located 1.5 links east of a north and south right-of-way fence on the west side of paved road.

59.550 Point for the center W 1/16 section corner of section 32, determined latitudinally by an east and west fence line and longitudinally, at proportionate distance, there is no remaining evidence of the original monument.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T1S R1E
S32
W 1/16 C ——— C
2004

S. 89° 54.3' W., beginning new measurement.

19.850 The 1/4 section corner of sections 31 and 32.

From the N 1/16 section corner of sections 32 and 33.

N. 89° 49.8' W., on the E-W centerline of the N 1/2 section 32.

19.615 The NE 1/16 section corner of section 32, monumented with a sandstone, 16x8x6 inches, loosely set and dimly marked, at the corner of fences projecting east, west and south.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S32
2004

Deposit the marked stone alongside the aluminum post.

S. 89° 57.4' W., beginning new measurement.

19.950 Point for the center N 1/16 section corner of section 32, at proportionate distance, falls in a north and south paved road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the paved road.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 32
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. 62° 30.2' W., 20.9 links distance, with aluminum cap marked: RM T1S R1E C-N 1/16 S32 13.8 FT 2004, with arrow pointing to the corner.

Reference monument is located 1.5 links east of a north and south right-of-way fence on the west side of paved road.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. 58° 08.7' W., 22.7 links distance, with aluminum cap marked: RM T1S R1E C-N 1/16 S32 15.0 FT 2004, with arrow pointing to the corner.

Reference monument is located 1.5 links east of a north and south right-of-way fence on the west side of paved road.

39.900

Point for the NW 1/16 section corner of section 21, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S32
2004

Set a 5 ft. steel fence post alongside the aluminum post.

59.850

The N 1/16 section corner of sections 31 and 32.

Dependent Resurvey of the Subdivision of Section 33
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 33 and 34.

S. 89° 48.4' W., on the E-W centerline of the S 1/2 of section 33.

20.007

The SE 1/16 section corner of section 33, at the corner of fences, projecting north, south and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S33
2004

Corner is located on the west side of fence corner.

S. 89° 50.6' W., beginning new measurement.

19.966

The center S 1/16 section corner of section 33, at the corner of fences, projecting north, west and southeast. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
E 1/16 | S33
C
2004

Corner is located on the northwest side of the fence corner.

N. 89° 54.6' W., beginning new measurement.

20.016

Point for the SW 1/16 section corner of section 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SW 1/16
S33
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 16.7 links west of a north and south fence line and 15.2 links north of an east and west fence line.

40.032 The S 1/16 section corner of sections 32 and 33.

From the true point for the 1/4 section corner of sections 33 and 34.

N. 89° 59.5' W., on the E-W centerline of section 33.

10.032 Point for the center E-E 1/64 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-E-E 1/64
S33
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 6 links south of an east and west fence line.

20.064 Point for the center E 1/16 section corner of section 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C——C
S33
2004

Corner is located 36.4 links south of an east and west gravel road, 3 links east of a north and south fence line, and 4.5 links south of an east and west fence line.

30.096 Point for the center W-E 1/64 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C-W-E 1/64
S33
2004

Corner is located 36.4 links south of the centerline of an east and west gravel road, and 3 links south of an east and west fence line.

40.128

Point for the center 1/4 section corner of section 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C 1/4
S33
2004

Corner is located 31.8 links south of a gravel road that projects east and curves to the northwest.

60.192

Point for the center W 1/16 section corner of section 33, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
W 1/16
C——C
S33
2004

Corner is located in an east and west fence line.

80.256

The 1/4 section corner of sections 32 and 33.

From the N 1/16 section corner of sections 33 and 34.

S. 89° 50.2' W., on the E-W centerline of the N 1/2 section 33.

10.004

Point for the center E-NE 1/64 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C-E-NE 1/64
S33
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the corner.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 7.6 links south of an east and west fence line.

20.008

Point for the NE 1/16 section corner of section 33, at proportionate distance, the original sandstone, 16x9x7 inches, plainly marked 1/16 and lying loose in a nearby ditch, was not used in the course of this survey.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S33
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 10.6 links south of an east and west fence line.

30.012

Point for the center W-NE 1/64 section corner of section 33.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-W-NE 1/16
S33
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 6.8 links south of an east and west fence line.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 33
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 40.016** The center N 1/16 section corner of section 33, monumented with a sandstone, 15x7x6 inches, plainly marked 1/16 and lying next to a fence corner with fences projecting north, south, east and west.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
N 1/16 | S33
C
2004

Corner is located on the northeast side of the fence corner.

N. 89° 48.8' W., beginning new measurement.

- 20.014** Point for the NW 1/16 section corner of section 23, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S33
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Corner is located in an east and west fence line, 16.6 links west of fence, projecting north and 38 links west of a fence projecting north and south.

- 40.028** The N 1/16 section corner of sections 32 and 33.
-

Survey of the Subdivision of Section 33
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the center E-E 1/64 section corner of section 33.

N. 0° 02.0' W., on the N-S centerline of the SE 1/4 of the NE 1/4 of section 33.

**SURVEY OF THE SUBDIVISION OF SECTION 33
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 19.965** The center E-NE 1/64 section corner of section 33.
-
- From the SE 1/16 section corner of section 33.
- N. 0° 16.7' W., on the N-S centerline of the E 1/2 of section 33.
- 20.066** The center E 1/16 section corner of section 33.
-
- From the NE 1/16 section corner of section 33.
- N. 0° 04.5' E., on the N-S centerline of the E 1/2 of section 33.
- 20.028** The E 1/16 section corner of sections 28 and 33.
-
- From the center W-E 1/64 section corner of section 33.
- N. 0° 07.7' E., on the N-S centerline of the SW 1/4 of the NE 1/4 section 33.
- 19.905** The center W-NE 1/64 section corner of section 33.
-
- From the center S 1/16 section corner of section 33.
- N. 0° 33.7' W., on the N-S centerline of section 33.
- 20.124** The center 1/4 section corner of section 33.
-
- From the center N 1/16 section corner of section 33.
- N. 0° 22.5' E., on the N-S centerline of section 33.
- 20.135** The 1/4 section corner of sections 28 and 33.
-
- Dependent Resurvey of the Subdivision of Section 34
by the Three Mile Method,
T. 1 S., R. 1 E., Uintah Special Meridian, Utah
-
- From the S 1/16 section corner of sections 34 and 35.
- N. 89° 37.4' W., on the E-W centerline of the S 1/2 of section 34.
- 19.948** The SE 1/16 section corner of section 34, monumented with a sandstone, 15x9x6 inches, firmly set and plainly marked 1/16 on north face.
- At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S34
2004

Deposit the marked stone alongside the aluminum post.

Raise a mound of stone, 3 ft. base, 2 ft. high, north of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

N. 89° 55.0' W., beginning new measurement.

20.017

The center S 1/16 section corner of section 34, at the corner of fences, projecting north, south and west. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
S 1/16 | S34
C
2004

Corner is located on the east side of a wood fence corner post.

N. 89° 58.1' W., beginning new measurement.

20.004

Point for the SW 1/16 section corner of section 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
SW 1/16
S34
2004

Raise a mound of stone, 4 ft. base, 3 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 3 links north of a new east and west fence line.

40.008

The S 1/16 section corner of sections 33 and 34.

From the 1/4 section corner of sections 34 and 35.

N. 89° 25.7' W., on the E-W centerline of section 34.

19.918

The center E 1/16 section corner of section 34, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set in concrete, projecting 12 inches above ground, with the original sandstone, 13x8x8 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
1/16
S34

Added the marks, BLM 2004, to the cap.

Corner is located at corner of fences projecting north and east.

Raise a mound of stone, 2 ft. base, 1 ft. high, west of galvanized pipe.

N. 89° 43.1' W., beginning new measurement.

19.952

The center 1/4 section corner of section 34, monumented with a sandstone, 13x12x8 inches, firmly set and plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C 1/4
S34
2004

Raise a mound of stone, with marked stone deposited inside mound, 3 ft. base, 2 ft. high, southeast of the aluminum post.

Corner is located on east side of a wood fence corner post with fences projecting west and south.

N. 89° 59.8' W., beginning new measurement.

20.060

Point for the center W 1/16 section corner of section 34, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 16 inches in the ground to bedrock, with a magnet at base, in a mound of stone, 4 ft. base to top of aluminum cap marked:

T1S R1E
W 1/16
C ——— C
S34
2004

Corner is located 4.2 links south of an east and west fence line and 22.7 links north of the center line of a gravel road that bears west and curves to the southeast.

40.120

The true point for the 1/4 section corner of sections 33 and 34.

From the N 1/16 section corner of sections 34 and 35.

N. 89° 13.4' W., on the E-W centerline of the N 1/2 of section 34.

19.945

The NE 1/16 section corner of section 34, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 12 inches above ground, with the original sandstone, 14x8x7 inches, dimly marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
1/16
S34

Added the marks, BLM 2004, to the cap.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

N. 89° 51.8' W., beginning new measurement.

20.000

The center N 1/16 section corner of section 34, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 16 inches above ground, with the original sandstone, 14x8x7 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap marked:

1959
1/16
S34

Added the marks, BLM 2004, to the cap.

Corner is located 1.5 links north of an east and west fence line.

N. 89° 50.4' W., beginning new measurement.

10.024

Point for the center E-NW 1/64 section corner of section 34.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-E 1/64
NW
S34
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 3.0 links north of an east and west fence line.

From which

A galvanized iron pipe, 2 1/2 inch diameter, bears S. 89° 08.7' W., 37.4 links distance, with a 3 inch threaded galvanized cap marked:

| LAND
| TRIBAL
| LAND

Added the marks, AM BLM 2004, to the cap.

The galvanized iron pipe is located at fence corner with fences projecting east and north.

The galvanized iron pipe was not used in the course of this survey.

15.036

Point for the center W-E-NW 1/256 section corner of section 34.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 34
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C-W-E-NW 1/256
S34
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on south edge of flat area.

- 20.048** The NW 1/16 section corner of section 34, monumented with a galvanized iron pipe, 2 1/2 inches diameter, firmly set, projecting 12 inches above ground, with the original sandstone, 14x10x8 inches, marked 1/16, deposited alongside, with a 3 inch threaded galvanized cap unmarked.

Add marks to the cap to read:

T1S R1E
NW 1/16
S34
BLM
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of galvanized pipe.

N. 89° 53.0' W., beginning new measurement.

- 20.012** The N 1/16 section corner of sections 33 and 34.

Survey of the Subdivision of Section 34
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the center E 1/16 section corner of section 34.

N. 0° 08.0' W., on the N-S centerline of the E 1/2 of section 34.

- 19.950** The NE 1/16 section corner of section 34.

From the 1/4 section corner of section 3 and 34 on the south boundary of the township, hereinbefore described.

N. 0° 01.3' W., on the N-S centerline of section 34.

**SURVEY OF THE SUBDIVISION OF SECTION 34
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

- 20.022** The center S 1/16 section corner of section 34.

N. 0° 12.9' E., beginning new measurement.
- 20.015** The center 1/4 section corner of section 34.

N. 0° 16.6' W., beginning new measurement.
- 19.900** The center N 1/16 section corner of section 34.

From the center E-NW 1/64 section corner of section 34.
N. 0° 06.9' W., on the N-S centerline of the NE 1/4 of the NW 1/4 of section 34.
- 19.866** The E-W 1/64 section corner of sections 27 and 34.

From the center W-E-NW 1/256 section corner of section 34.
N. 0° 04.5' W., on the N-S centerline of the W 1/2 of the NE 1/4 of the NW 1/4 of section 34.
- 19.886** The W-E-W 1/256 section corner of sections 27 and 34.

From the center W 1/16 section corner of section 34.
N. 0° 14.9' W., on the N-S centerline of the W 1/2 of section 34.
- 19.955** The NW 1/16 section corner of section 34.

Dependent Resurvey of a Portion of the Subdivision of Section 35
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the S 1/16 section corner of sections 35 and 36.
S. 89° 44.3' W., on the E-W centerline of the S 1/2 of section 35.
- 20.105** The SE 1/16 section corner of section 35, at the corner of fences, projecting north and east. This position is harmoniously related to other identified original corners in the area, and is accepted as the best available evidence of the original corner position.
At the corner point

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 35
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
SE 1/16
S35
2004

Corner is located on west side of the wood fence pose.

From which

A rebar with a yellow cap, marked: RLS 5039, bears S. 10° 18.4' W., 6.7 links distance.

This rebar was not used in the course of this survey.

From the 1/4 section corner of sections 35 and 36.

S. 89° 50.2' W., on the E-W centerline of section 35.

20.028

Point for the center E 1/16 section corner of section 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C——C
S35
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 2.3 links west of a north and south fence line.

40.056

Point for the center 1/4 section corner of section 35, at proportionate distance, falls in hay field, there is no remaining evidence of the original corner, not monumented.

60.084

Point for the center W 1/16 section corner of section 35, at proportionate distance, falls in hay field, there is no remaining evidence of the original corner, not monumented.

80.112

The 1/4 section corner of sections 34 and 35.

From the true point for the N 1/16 section corner of section 35 and 36.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 35
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

S. $89^{\circ} 46.8'$ W., on the E-W centerline of the N $1/2$ of section 35.

20.054

Point for the NE $1/16$ section corner of section 35, at proportionate distance, falls on the west edge of a dirt road, there is no remaining evidence of the original corner.

Set a railroad spike flush with the road.

This spike is located 10.6 links W of the centerline of road and 39.4 links west of a north and south fence line.

From which

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears N. $49^{\circ} 29.7'$ E., 49.2 links distance, with aluminum cap marked: RM T1S R1E NE $1/16$ S35 32.5 FT 2004, with arrow pointing to the corner.

Reference monument is located in a north and south fence line on the east side of dirt road.

An aluminum post, 30 inches long, 2 1/2 inches diameter, set 24 inches in the ground, with a magnet at base, for a reference monument, bears S. $46^{\circ} 44.5'$ E., 51.2 links distance, with aluminum cap marked: RM T1S R1E NE $1/16$ S35 33.8 FT 2004, with arrow pointing to the corner.

Reference monument is located in a north and south fence line on the east side of dirt road.

40.108

Point for the center N $1/16$ section corner of section 35, at proportionate distance, falls in pond, there is no remaining evidence of the original corner, not monumented.

60.162

Point for the NW $1/16$ section corner of section 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW $1/16$
S35
2004

Raise a mound of stone, 3 ft. base, 2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 35
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Corner is located 2.2 links west of a north and south fence line.

80.216 The N 1/16 section corner of sections 34 and 35.

Survey of the Subdivision of Section 35
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the point for the E 1/16 section corner of sections 2 and 35,
on the south boundary of the township, hereinbefore described.

N. 0° 05.6' W., on the N-S centerline of the E 1/2 of section 35.

19.891 The SE 1/16 section corner of section 35.

N. 0° 28.2' E., beginning new measurement.

19.995 The center E 1/16 section corner of section 35.

N. 0° 10.6' E., beginning new measurement.

19.939 The NE 1/16 section corner of section 35.

N. 0° 10.6' E., beginning new measurement.

19.939 The E 1/16 section corner of sections 26 and 35.

From the point for the center W 1/16 section corner of section 35.

N. 0° 01.4' E., on the N-S centerline of the W 1/2 of section 35.

9.950 Point for the center S-NW 1/64 section corner of sections 35.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24
inches in the ground, with a magnet at base, with aluminum cap
marked:

T1S R1E
C-S-NW 1/64
S35
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in an east and west fence line, 4.5 links west of
its intersection with a north and south fence line.

**SURVEY OF THE SUBDIVISION OF SECTION 35
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS**19.900**

The NW 1/16 section corner of section 35.

N. 0° 01.4' E., beginning new measurement.

19.900

The W 1/16 section corner of sections 26 and 35.

From the center S-NW 1/64 section corner of section 35.

S. 89° 48.5' W., on the E-W centerline of the SW 1/4 of the NW 1/4 of section 35.

20.041

The S-N 1/64 section corner of sections 34 and 35.

Dependent Resurvey of a Portion of the Subdivision of Section 36
by the Three Mile Method
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the 1/4 section corner of section 31 and 36, on the east boundary of the township, hereinbefore described.

N. 89° 58.6' W., on the E-W centerline of section 36.

19.870

Point for the center E 1/16 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
E 1/16
C — C
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on east side of a cow pasture and 36.4 links west of a north and south fence line.

39.740

Point for the center 1/4 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH**

CHAINS

T1S R1E
C 1/4
S36
2004

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of the aluminum post.

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located in a cow pasture.

59.610

Point for the center W 1/16 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with a magnet at base, with aluminum cap marked:

W 1/16
C ——— C
S34
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located on the northwest side of farm land and on the east bank of a wash.

79.480

The 1/4 section corner of sections 35 and 36.

From the N 1/16 section corner of sections 31 and 36, on the east boundary of the township, hereinbefore described.

N. 89° 59.1' W., on the E-W centerline of the N 1/2 of section 36.

19.857

Point for the NE 1/16 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NE 1/16
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

From this corner, a rebar with a red cap marked: PLS 144102, bears S. 60° 24.8' E., 26.4 links distance. The rebar is located in the corner of fences projecting south and west. The rebar or fence was not used in the course of this survey.

39.714

Point for the center N 1/16 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
C
N 1/16 | S36
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located about 75 links north of a field in tall grass.

59.671

Point for the NW 1/16 section corner of section 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T1S R1E
NW 1/16
S36
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 5 links south of a ditch, and 30 links north of the north edge of a field.

79.314

Point selected for the witness corner to the N 1/16 section corner of sections 35 and 36.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

WC
T1S R1W
N 1/16
← S35 | S36
2004

**DEPENDENT RESURVEY OF THE SUBDIVISION OF SECTION 36
BY THE THREE MILE METHOD,
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH**

CHAINS

Set a 5 ft. steel fence post alongside the aluminum post.

79.428 The true point for the N 1/16 section corner of sections 35 and 36.

Survey of the Subdivision of Section 36
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

From the NE 1/16 section corner of section 36.

N. 0° 08.9' E., on the N-S centerline of the E 1/2 of section 36.

19.967 The E 1/16 section corner of sections 25 and 36.

From the center 1/4 section corner of section 36.

N. 0° 11.0' E., on the N-S centerline of the E 1/2 of section 36.

19.965 The center N 1/16 section corner of section 36.

N. 0° 11.0' E., beginning new measurement.

19.965 The 1/4 section corner of sections 25 and 36.

Dependent Resurvey of Mineral Survey No. 5519
Duchesne Nos. 6 and 7
T. 1 S., R. 1 E., Uintah Special Meridian, Utah

The center N 1/16 section corner of section 4, T. 2 S., R. 1 E., monumented with a sandstone, 14x9x7 inches, firmly set, 12 inches in the ground and plainly marked 1/16 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

T2S R1E
C
N 1/16 | S4
C
2004

Set a 5 ft. steel fence post alongside the aluminum post.

Corner is located 45 links north of an east and west fence line.

SURVEY OF THE SUBDIVISION OF SECTION 36
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS

From this corner, the 1/4 section corner of sections 4 and 33, Ts. 1 and 2 S., R. 1 E. hereinbefore described, bears N. $0^{\circ} 25.0'$ E., 21.451 chains distance.

Note: No original corner monuments for Mineral Survey No. 5519 were recovered during the course of this resurvey. Subsequently, all corners were reestablished at record bearing and distance, beginning at the center N 1/16 section corner of section 4, T. 2 S., R. 1 E.

From the point for corner No. 3, Duchesne No. 5, identical with corner No. 4, Duchesne No. 6, Mineral Survey No. 5519.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

MS 5519
 D6 4
 3
 D5
 2004

Set a 5 ft. steel fence post alongside the aluminum post.

From this corner, the center N 1/16 section corner of section 4, T. 2 S., R. 1 E., bears S. $29^{\circ} 48.0'$ W., 3.546 chains distance, hereinbefore described.

N. $37^{\circ} 18.0'$ W., on line 4-1 of Duchesne No. 6.

22.727

Point for Corner No. 1, Duchesne No. 6, identical with corner No. 1, Duchesne No. 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

MS 5519
 D7 1
 1
 D6
 2004

Set a 5 ft. steel fence post alongside the aluminum post.

From this corner, the 1/4 section corner of sections 4 and 33, T. 1 and 2 S., R. 1 E., hereinbefore described, bears N. $88^{\circ} 36.5'$ E., 12.170 chains distance.

S. $52^{\circ} 42.0'$ W., on line 1-2 of Duchesne Nos. 6 and 7.

DEPENDENT RESURVEY OF MINERAL SURVEY NO. 5519
DUCHESNE NOS. 6 AND 7
T. 1 S., R. 1 E., UTAH SPECIAL MERIDIAN, UTAH

CHAINS**9.091**

Point for Corner No. 2. Duchesne No. 6, identical with Corner No. 2, Duchesne No. 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

MS 5519
 D7
 2
 2 D6
 2004

Set a 5 ft. steel fence post alongside the aluminum post.

N. 37° 18.0' W., on line 2-3 of Duchesne No. 7.

7.248

Intersect the section line between sections 4 and 33, Ts. 1 and 2 S., R. 1 E. hereinbefore described.

22.727

Point for corner No. 3, Duchesne No. 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

MS 5519
 3
 D7
 2004

Set a 5 ft. steel fence post alongside the aluminum post.

N. 52° 42.0' E., on line 3-4 of Duchesne No. 7.

9.091

Point for Corner No. 4, Duchesne No. 7.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with a magnet at base, with aluminum cap marked:

4
 MS 5519
 D7
 2004

From this corner, the SW 1/16 section corner of section 33, bears N. 69° 21.4' E., 6.183 chains distance.

S. 37° 18.0' E., on line 4-1 of Duchesne No. 7.

DEPENDENT RESURVEY OF MINERAL SURVEY No. 5519
DUCHESNE NOS. 6 AND 7
T. 1 S., R. 1 E., UINTAH SPECIAL MERIDIAN, UTAH

CHAINS

- 22.381** Intersect the section line between sections 4 and 33, Tsp. 1 and 2 S., R. 1 E., hereinbefore described.
- 22.727** Corner No. 1, Duchesne No. 7, identical with corner No. 1, Duchesne No. 6, hereinbefore described.
-

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS
T. 1 S., R. 1 E., USM, Utah

Name	Capacity
Glen B. Hatch	Cadastral Surveyor
Scott Bishop	Survey Technician
Tyler Trujillo	Survey Technician
Brandon Sanchez	Survey Technician
Manuel R. Velez-Tuero	Survey Technician
Adrian Kurip	Survey Technician

CERTIFICATE OF SURVEY

I, **M. Ross Workman, Supervisory Cadastral Surveyor**, hereby certify upon honor that, in pursuance of Special Instruction bearing the date of the **30th day of April, 2004**, I have dependently resurveyed portions of the south and east boundaries, a portion of the subdivisional lines, a portion of the subdivision of certain sections by the Three Mile Method, the survey of the subdivision of certain sections and the dependent resurvey of Mineral Survey No. 5519, in Township 1 South, Range 1 East,

of the Uintah Special Meridian, in the State of Utah, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

October 1, 2005
Date


Supervisory Cadastral Surveyor

CERTIFICATE OF APPROVAL


BUREAU OF LAND MANAGEMENT
SALT LAKE CITY, UTAH

The foregoing field notes of the dependent resurvey of portions of the south and east boundaries, a portion of the subdivisional lines, a portion of the subdivision of certain sections by the Three Mile Method, the survey of the subdivision of certain sections and the dependent resurvey of Mineral Survey No. 5519, in Township 1 South, Range 1 East, Uintah Special Meridian, Utah,

executed by **M. Ross Workman, Supervisory Cadastral Surveyor**,

having been critically examined and found correct, are hereby approved.

October 7, 2005
Date


Chief Cadastral Surveyor of Utah